

G-6236172

VERY IMPORTANT: THIS LABEL IS ATTACHED TO THE RIFLE AND MUST REMAIN WITH IT AT ALL TIMES.

Remington®

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

SERIAL NO. 66236172
ORDER NO. 25716

46

Made in Illinois, U.S.A. Pat. & Lic. Off. Marca Registrada. Marque Deposee.

13RW

5716 66236172

ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

UPC



ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

UPC



SERIAL NO.



M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO


- INSTRUCTION BOOK 3518

46 FORM

proof of purchase




owner registration sticker



ORDER NO.	25716
BARREL LENGTH	24"
CAPACITY	6

G6236172



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # 6023 6172

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		9/5/02	RL
600	PROOF			
607	CHECK HEADSPACE		9/9/02	RL
610	DIS-ASSEMBLE GUN		9/9/02	RL
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	INSPECTED SEP 10 2002 OPERATOR RK		
615	ROLLMARK CALIBER		9/10	BS
617	DRILL AND TAP SIGHT HOLES		9-12-02	K
620	APPLY COATINGS (BARREL ACTION)		9-18	TA
	(BOLT)		9-18	TA
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-20-02	RW
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-20-02	RW
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-20-02	RW
	D) OIL FIRING PIN ASSEMBLY		9-20-02	RW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS		11-2-02	RL

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>5.5</u> <u>5.5</u> <u>5.0</u>	10-4-02	DA
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.0</u> <u>3.0</u> <u>3.0</u>	10-4-02	DA
	H) TRIGGER PULL TEST AND RETAINABILITY		11-12-02	RL
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.021</u> <u>.022</u>	10-4-02	DA
	J) ASSEMBLE STOCK		9-23-02	RW
	K) ASSEMBLE SWIVEL STUDS		11-12-02	RL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		10/31/02	RL
	M) IRON SIGHT ALIGNMENT		10/31/02	RL
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10/31/02	RL
640	GALLERY TEST AND TARGET	PASS FAIL	10-4-02	A
	MALFUNCTION	CORRECTION	10-4-02	A
	MALFUNCTION	CORRECTION	10-4-02	A
	MALFUNCTION	CORRECTION	10-4-02	A
	MALFUNCTION	CORRECTION	10-4-02	A
645	INSPECT FOR LIVE AMMO		10-4-02	A
655	FINAL INSPECTION A) HEADSPACE		11-12-02	RL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.43</u> <u>2.56</u> <u>2.55</u> <u>2.51</u> <u>2.31</u>	10-4-02	DA
	C) FUNCTION		11-12-02	RL
660	PACK		11-12-02	DA

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.34	2.28		2.54	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2
PULL #2	2.48	2.65		2.65	
PULL #3	2.25	2.26		2.46	
PULL #4	2.37	2.44		2.44	
PULL #5	2.21	2.24		2.48	
TOTAL	11.65	11.87		12.57	
AVG.	2.33	2.37		2.51	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.18	3.34		
PULL #2	3.32	3.21		
PULL #3	3.31	3.41		
PULL #4	3.34	3.24		
PULL #5	3.26	3.32		
TOTAL	16.41	16.52		
AVG.	3.28	3.30		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCUR
PULL #1	4.25	4.17		4.05
PULL #2	4.20	4.24		4.07
PULL #3	4.24	4.29		4.04
PULL #4	4.25	4.27		4.03
PULL #5	4.32	4.27		4.23
TOTAL	21.26	21.24		20.42
AVG.	4.25	4.24		4.08

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6236172.___0

FILE DATE AND TIME: 10/05/2002 10:19

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES


The Average X Centroid of the Five Target Set:	-0.103
The Average Y Centroid of the Five Target Set:	-0.061
The Average Point of Impact of the Five Target Set:	0.120
The Average Mean Radius of the Five Target Set:	0.784
The Distance from POA to Centroid Target #1:	0.039
The Distance from Centroid Target #2 to Centroid Target #1:	0.064
The Distance from Centroid Target #3 to Centroid Target #1:	0.388
The Distance from Centroid Target #4 to Centroid Target #1:	0.057
The Distance from Centroid Target #5 to Centroid Target #1:	0.139

BARBER - M24 0146838

SERIAL NUMBER: G6236172. __0
 TARGET NUMBER: 1
 FILE DATE: 10/05/2002
 FILE TIME: 10:19

POINT#	X	Y
1:	0.549	-1.843
2:	0.107	-0.694
3:	0.262	-0.533
4:	0.235	-0.182
5:	-0.748	-0.101
6:	-0.291	0.145
7:	0.010	0.302
8:	-0.218	0.644
9:	0.330	1.098
10:	-0.478	1.474

X CENTROID: -0.024
 Y CENTROID: 0.031
 POA TO CENTROID: 0.039
 HORZ SPREAD: 1.297
 VERT SPREAD: 3.317
 GROUP SPREAD: 3.472
 MIN RADIUS: 0.273
 MAX RADIUS: 1.960
 MEAN RADIUS: 0.824
 # IN 1 IN DIAMETER: 3
 # IN 2 IN DIAMETER: 7
 # in 3 IN DIAMETER: 8



TARGET APPROX 1/2 SCALE

BARBER - M24 0146839

SERIAL NUMBER: G6236172. 0

TARGET NUMBER: 2

FILE DATE: 10/05/2002

FILE TIME: 10:19

POINT#	X	Y
1:	0.531	-1.502
2:	-0.071	-0.697
3:	0.410	-0.369
4:	0.701	0.003
5:	0.353	0.170
6:	0.421	0.936
7:	-0.399	0.661
8:	-0.583	0.180
9:	-0.892	-0.164
10:	-1.332	1.239

X CENTROID: -0.086

Y CENTROID: 0.046

POA TO CENTROID: 0.097

HORZ SPREAD: 2.033

VERT SPREAD: 2.741

GROUP SPREAD: 3.314

MIN RADIUS: 0.456


MAX RADIUS: 1.725

MEAN RADIUS: 0.909

IN 1 IN DIAMETER: 1

IN 2 IN DIAMETER: 7


in 3 IN DIAMETER: 8



TARGET APPROX 1/2 SCALE

BARBER - M24 0146840


SERIAL NUMBER: G6236172. __0	POINT#	X	Y
TARGET NUMBER: 3	1:	-0.581	-1.039
FILE DATE: 10/05/2002	2:	-0.432	-0.881
FILE TIME: 10:19	3:	-0.537	-0.752
	4:	-0.957	-0.058
X CENTROID: -0.219	5:	-0.382	-0.002
Y CENTROID: -0.305	6:	0.166	-0.624
POA TO CENTROID: 0.375	7:	-0.070	-0.409
HORZ SPREAD: 1.189	8:	0.174	-0.191
VERT SPREAD: 1.872	9:	0.197	0.076
GROUP SPREAD: 2.041	10:	0.232	0.833
MIN RADIUS: 0.182			
MAX RADIUS: 1.224			
MEAN RADIUS: 0.598			
# IN 1 IN DIAMETER: 3			
# IN 2 IN DIAMETER: 9			
# in 3 IN DIAMETER: 10			



TARGET APPROX 1/2 SCALE

BARBER - M24 0146841

SERIAL NUMBER: G6236172. __0	POINT#	X	Y
TARGET NUMBER: 4	1:	0.571	-1.079
FILE DATE: 10/05/2002	2:	0.703	-0.702
FILE TIME: 10:19	3:	-0.353	-0.991
	4:	0.236	-0.023
X CENTROID: -0.058	5:	1.142	0.760
Y CENTROID: -0.015	6:	-0.084	0.393
POA TO CENTROID: 0.060	7:	-0.489	0.120
HORZ SPREAD: 2.218	8:	-0.512	0.588
VERT SPREAD: 1.839	9:	-0.717	0.394
GROUP SPREAD: 2.302	10:	-1.076	0.385
MIN RADIUS: 0.294			
MAX RADIUS: 1.429			
MEAN RADIUS: 0.849			
# IN 1 IN DIAMETER: 3			
# IN 2 IN DIAMETER: 5			
# in 3 IN DIAMETER: 10			




TARGET APPROX 1/2 SCALE

BARBER - M24 0146842

SERIAL NUMBER: G6236172. __0
TARGET NUMBER: 5
FILE DATE: 10/05/2002
FILE TIME: 10:19

POINT#	X	Y
1:	0.111	-1.582
2:	-0.111	-0.589
3:	0.659	-0.049
4:	0.541	0.140
5:	-0.249	0.104
6:	-0.497	0.175
7:	-0.865	-0.111
8:	-0.823	0.359
9:	-0.466	0.967
10:	0.435	-0.041

X CENTROID: -0.126
Y CENTROID: -0.063
POA TO CENTROID: 0.141
HORZ SPREAD: 1.524
VERT SPREAD: 2.549
GROUP SPREAD: 2.613
MIN RADIUS: 0.207
MAX RADIUS: 1.538
MEAN RADIUS: 0.739
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 8
in 3 IN DIAMETER: 9



TARGET APPROX 1/2 SCALE