

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 10 / 08 / 03Inspector: BLRRound Level: 3761☒ Measure Headspace min - .006☒ Sear Engagement: 1st. .0250 2nd. .0245 3rd. .0243 Ave. .0246 spec- .020" to .025" 83☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Trigger Pull: 1st. 4.116 2nd. 4.143 3rd. 4.235 Ave. 4.164 spec- 4 lb. to 5.5 lb.☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: normal wear wear on Bolt stop☒ Inspect stock for any signs of cracking or other failure. cracks in stock☒ Other items ofnote: magazine box some protrusion- Photos taken of chamber w/ scope 3 front / 3 rear- Broken magazine latch / replaced with Ripra A12 Latch

TLW1216

Remington Confidential

ET22489