

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-5

TLW #: TLW1216

Date: 8 / 20 / 03Inspector: SW/BLRound Level: 221

- ☒ Measure Headspace min+.006
- ☒ Sear Engagement: 1st..0266 2nd..0267 3rd..0269 Ave. .02673 spec- .020" to .025" 83
- ☒ Reset Sear Engagement if Required: 1st..0214 2nd..0220 3rd..0219 Ave. .02176
- ☒ Trigger Pull: 1st.4.953 2nd.5.004 3rd.5.131 Ave. 5.029 spec- 4 lb. to 5.5 lb.
- ☒ ~~Reset~~ Trigger Pull if Required: 1st.4.861 2nd.5.001 3rd.4.954 Ave. 4.939
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear
- ☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock, crack on middle take down screw hole.
- ☒ Other items of note: Top of magazine box has some protrusion, wear in magazine latch area

TLW1216

Remington Confidential

ET22511