

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-5

TLW #: TLW1216

Date: 9 / 10 / 03Inspector: EW/BLRound Level: 1241☒ Measure Headspace Min 4.007☒ Sear Engagement: 1st. .0239 2nd. .0236 3rd. .0236 Ave. .0236 spec- .020" to .025"☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Trigger Pull: 1st. 4.648 2nd. 4.549 3rd. 4.620 Ave. 4.606 spec- 4 lb. to 5.5 lb.☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear, Bolt stop OK☒ Inspect stock for any signs of cracking or other failure: cracks in stock☒ Other items of

note: Top of magazine box has some protrusion, wear in magazine
latch area - Extractor inside Bolt head not extracting properly.

TLW1216

Remington Confidential

ET22529