

GUN # A-4
SERIAL # 71126317
CAL 300 WIN MAG

DAT # 1 M / 710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216
PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
SW/BL	7/21/03	Weight	8.121 TLW1216 Am		
SW/BL	7/21/03	Head space	Min +.005 TLW1216 A		
SW/BL	7/21/03	Head space	Shoulder Gauge .221 will not close up TLW1216 A		
SW/BL	7/21/03	Firing Pin Indent	.019 - .019 - .019 Avg. .019 TLW1216 D		
SW/BL	7/22/03	Balance Point	From Butt Pad 19.7" TLW1216 AN		
SW/BL	7/22/03	Trigger Pull	5.482, 5.379, 5.433 Avg. 5.431 TLW1216 F		
SW/BL	7/22/03	Sens/Trigger Engagement	.0287, .0279, .0283 Avg. .0283 TLW1216 E		
SW/BL	7/22/03	Sens Left	.0232 TLW1216 E		
SW/BL	7/22/03	Reset Sear/Trigger Engagement	.0245, .0247, .0247 Avg. .02463 TLW1216 E		
SW/BL	7/22/03	Reset Trigger Pull	5.447, 5.521, 5.410 Avg. 5.459 TLW1216 F		
SW/BL	7/22/03	Firing Pin Head / Sear Engagement	.064 TLW1216 E		
SW/BL	7/23/03	Safety ON Forces	5.055, 4.990, 4.935 Avg. 4.993 TLW1216 G		
SW/BL	7/23/03	Safety OFF Forces	2.380, 2.160, 2.035 Avg. 2.192 TLW1216 G		
SW/BL	7/24/03	Bolt Lift	16.04, 17.28, 15.92 Avg. 16.41 TLW1216 H		
SW/BL	7/24/03	Bolt Close	5.74, 5.78, 5.64 Avg. 5.72 TLW1216 H		
SW/BL	7/24/03	Bolt Lift w/ Dummy	16.64, 14.64, 15.58 Avg. 15.62 TLW1216 H		
SW/BL	7/24/03	Bolt Close w/ Dummy	6.92, 5.68, 5.64 Avg. 6.08 TLW1216 H		
SW/BL	7/25/03	Magazine Spring Force	gauge 0.200 1.810 - 1.765 - 1.755 - Avg. 1.776 TLW1216 I		
SW/BL	7/29/03	Magazine Capacity Test	gauge 1.04 1.055 - 4.080 - 4.560 - Avg. 4.231 TLW1216 O		
SW/BL	7/29/03	Check Iss system	pass - weak ejection TLW1216 AI		
SW/BL	7/29/03	Twist Rate	1 Turn 10" TLW1216 AN		
SW/BL	7/30/03	Bore diameter	spec. 307/301 Dimension .300 TLW1216 L		
SW/BL	7/30/03	Chamber Cast / measurements	See spread sheet TLW1216 K		
SW/BL	7/30/03	Groove diameter	spec. 308/309 Dimension .3073 TLW1216 M		
SW/BL	8/6/03	Proof Test Hammer bolt up & back. Bolt Head broke	sign of lockup and case stuck in bolt, TLW1216 B	1	1
		Ejector stuck back.			
SW/BL	8/6/03	Head space After Proof (See Proof Test)	TLW1216 C		
SW	8/7/03	Took Bolt From B-2 and Put in A-4			
SW/BL	8/7/03	Head space	Min +.005 TLW1216 A		
SW/BL	8/7/03	Proof Test Hammer Bolt back	TLW1216 B	1	2
SW/BL	8/7/03	Head space After Proof	Min +.007 TLW1216 C		
SW/BL	8/8/03	Basic Jack Function Test	1SH TLW1216 P	200	202
Bob Lee	8/12/03	Basic Shoulder Function Test	0 Min / Functions TLW1216 Q	20	222

Logform

BARBER - 5.22.067005537

Confidential - BARBER - 5.22.067005537 Order

Williams V. Remington

ET22537