

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-4

TLW #: TLW1216

Date: 8 / 20 / 03Inspector: SW/BLRound Level: 222

- ☒ Measure Headspace min⁺.007.
- ☒ Sear Engagement: 1st. .0249 2nd. .0249 3rd. .0250 Ave. .02493 spec. .020" to .025" 83
- ☐ Reset Sear Engagement if Required: 1st. 2nd. 3rd. Ave.
- ☒ Trigger Pull: 1st. 4.219 2nd. 4.412 3rd. 4.336 Ave. 4.320 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. 2nd. 3rd. Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: very little wear on bolt stop
- ☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock
crack on middle take down screw hole
- ☒ Other items of note: Top of magazine box has some protrusion, wear in
magazine latch area

TLW1216

Remington Confidential

ET22542