

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-3

TLW #: TLW1216

Date: 9 / 3 / 03Inspector: SWRound Level: 841☒ Measure Headspace Min 4.008☒ Sear Engagement: 1st. .0244 2nd. .0244 3rd. .0244Ave. .0244 spec. .020" to .025"☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____

Ave. _____

☒ Trigger Pull: 1st. 3.937 2nd. 4.015 3rd. 3.896Ave. 3.949 spec. 4 lb. to 5.5 lb.☒ Reset Trigger Pull if Required: 1st. 4.917 2nd. 4.933 3rd. 4.702Ave. 4.847☒ Inspect cam surface, locking lugs and bolt stop for signs of excessivewear: Normal wear, little wear on bolt stop.☒ Inspect stock for any signs of cracking or otherfailure. Cracks in stock☒ Other items ofnote: Top of magazine box has some protrusion, wear in magazine latch area.

TLW1216

Remington Confidential

ET22567