

GUN # A-2

SERIAL # 71126307

CAL 300 WIN MAG

DAT # 1 M710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216

PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS RDS. FIRED	AT START-0 TOTAL RDS.
SW/BL	7/21/03	Weight	8.427 TLW 1216 AM		
SW/BL	7/21/03	Head Space	Min +.001 TLW1216A		
SW/BL	7/21/03	Head Space	Shoulder Gauge .321 Will not close up TLW1216A		
SW/BL	7/21/03	Firing Pin Indent	.020 - .021 - .022 Avg. .021 TLW1216B		
SW/BL	7/22/03	Balance Point	From Butt Pad 19.5" TLW1216AN		
SW/BL	7/22/03	Trigger Pull	4.666, 4.727, 4.601 Avg 4.664 TLW1216F		
SW/BL	7/22/03	Sear/Trigger Engagement	.0290, .0296, .0290 Avg. .0292 TLW1216E		
SW/BL	7/22/03	Sear Lock	.0235 TLW1216E		
SW/BL	7/22/03	Reset Sear/Trigger Engagement	.0246, .0245, .0247 Avg. .0246 TLW1216E		
SW/BL	7/22/03	Reset Trigger Pull	4.428, 4.447, 4.540 Avg. 4.471 TLW1216F		
SW/BL	7/22/03	Firing Pin Head/Sear Engagement	.061 TLW1216E		
SW/BL	7/23/03	Safety ON Forces	5.005, 5.180, 5.205 Avg 5.130 TLW1216G		
SW/BL	7/23/03	Safety OFF Forces	2.245, 2.068, 2.105 Avg 2.138 TLW1216G		
SW/BL	7/24/03	Bolt Lift	15.94, 17.12, 17.22 Avg 16.76 TLW1216H		
SW/BL	7/24/03	Bolt Close	6.18, 5.54, 5.76 Avg 5.82 TLW1216H		
SW/BL	7/24/03	Bolt Lift w/Dummy	16.04, 16.00, 14.68 Avg 15.57 TLW1216H		
SW/BL	7/24/03	Bolt Close w/Dummy	7.14, 5.68, 6.08 Avg 6.30 TLW1216H		
SW/BL	7/25/03	Magazine Spring Force	Gauge 0.200 1.980 - 1.880 - 1.880 Avg 1.913 TLW1216I		
SW/BL	7/29/03	Magazine Capacity Test	Gauge 1.0" (4.645 - 4.740 - 4.770 Avg. 4.518 TLW1216C)		
SW/BL	7/29/03	Check Ejector System	Pass - Weak Ejection TLW1216AI		
SW/BL	7/29/03	Twist Rate	1 Turn 10" + .25 TLW1216AN		
SW/BL	7/30/03	Bore diameter	Spec .308/.309 Dimension .309 TLW1216L		
SW/BL	7/30/03	Chamber Cast/measurements	See spread sheet TLW1216K		
SW/BL	7/30/03	Groove diameter	Spec .308/.309 Dimension .3093 TLW1216M		
SW/BL	8/6/03	Proof Test (Hammer bolt up back, signs of locking)	TLW1216B		
		2nd case stuck in bolt, ejector stuck back.			
SW/BL	8/6/03	Head Space After Proof	Min (See Proof Test) TLW1216C	1	1
SW	8/7/03	Took Bolt From B-1 and Put in A-2			
SW/BL	8/7/03	Head Space	Min +.001 TLW1216A		
SW/BL	8/7/03	Proof Test	Hammer bolt Back TLW1216B		
SW/BL	8/7/03	Head Space After Proof	Min +.001 TLW1216C	1	2
SW/BL	8/8/03	Basic Jack Function Test	0 malfunctions TLW1216P	200	202
Jeff C	8/12/03	Basic Shoulder Function Test	0 Malfunctions TLW1216Q	20	222

Logform

BARBER - 5-22-06 0005570

Confidential - SHARPER - 5-22-06 0005570 Order

Williams v. Remington

ET22570