

GUN # A-13

DAT # 1 M / 710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216
PROJECT #241314

SERIAL # 71126321

CAL 300 WIN MAG

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS RDS. FIRED	AT START-0 TOTAL RDS.
SW/BL	7/21/03	Head space	Min +.005	TLW1216A	
SW/BL	7/21/03	Head space	Shoulder Gauge .321 will not close up	TLW1216A	
SW/BL	7/21/03	Firing Pin Indents	.019 - .015 .020 Avg. .0193	TLW1216D	
SW/BL	7/22/03	Trigger Pull	5.215, 5.264, 5.248 Avg 5.242	TLW1216F	
SW/BL	7/22/03	Sear Trigger Engagement	.0282, .0282, .0280 Avg. .02813	TLW1216E	
SW/BL	7/22/03	Sear Lift	.0218	TLW1216E	
SW/BL	7/22/03	Reset Sear Trigger Engagement	.0251, .0249, .0249 Avg. .02496	TLW1216E	
SW/BL	7/22/03	Trigger Pull	5.209, 5.366, 4.942 Avg 5.072	TLW1216F	
SW/BL	7/22/03	Firing Pin Head/Sear Engagement	.063	TLW1216E	
SW/BL	7/23/03	Safety ON Forces	4.848, 4.810, 4.995 Avg 4.880	TLW1216G	
SW/BL	7/23/03	Safety OFF Forces	2.220, 2.075, 2.075 Avg 2.107	TLW1216G	
SW/BL	7/24/03	Bolt Lift	16.16, 16.64, 16.22 Avg. 16.34	TLW1216H	
SW/BL	7/24/03	Bolt Close	6.02, 5.98, 5.32 Avg. 5.77	TLW1216H	
SW/BL	7/24/03	Bolt Lift w/Dummy	16.48, 16.06, 16.02 Avg. 16.18	TLW1216H	
SW/BL	7/24/03	Bolt Close w/Dummy	6.24, 6.18, 6.24 Avg. 6.22	TLW1216H	
SW/BL	7/25/03	Magazine Spring Force	gauge 0.200 1.705 - 1.760 - 1.765 Avg 1.703	TLW1216I	
SW/BL	7/29/03	Magazine Capacity Test	gauge 1.0 4.375 - 4.950 - 5.385 Avg. 4.903	TLW1216D	
SW/BL	7/29/03	Check Eject System	pass weak ejection	TLW1216AI	
SW/BL	7/29/03	Twist Rate	1 Turn 10"	TLW1216N	
SW/BL	7/30/03	Bore diameter	Spec .300/301 Dimension .300	TLW1216L	
SW/BL	8/6/03	Proof Test	Hammer bolt break	TLW1216B	1
SW/BL	8/6/03	Head space After Proof	Min +.006	TLW1216C	
SW/BL	8/20/03	Inspection	Checked stock for cracks, stock has cracks	TLW1216	
SW/BL	9/11/03	SAAMI JAR OFF TEST	PASS	TLW1216X	
SW/BL	9/12/03	SAAMI ROTATION TEST	PASS	TLW1216Y	
SW/BL	9/12/03	SAAMI DROP TEST	PASS	TLW1216W	
SW/BL	9/18/03	Extended 18" JAR-Off Test	PASS	TLW1216Z	
SW/JS	9/19/03	EXTENDED 24" JAR-Off Test	PASS	TLW1216Z	
SW/JS	9/19/03	EXTENDED 48" JAR-Off Test	FAIL	TLW1216Z	
SW	9/25/03	Head space	Min +.6 OK		
BL/JSims	10/22/03	Scope mount / Scope	used Torque wrench to torque mount at 25 in Lbs. / Scope 40 in Lbs.		
B.Lee/JSims	10/23/03	Accuracy #1	5-5 shot groups - 5 failing mg shots	TLW1216T	30 37

Logform

BARBER - 5.22.06/0005583

Confidential - SHARPER - 5022660005583 Order

Williams V. Remington

ET22583