

TLW 1216X

Project No. 241314

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**JAR-OFF TEST**

Firecontrol No. A-13 Firecontrol Type: Standard Date: 9-11-03
 Dry Cycles/Rounds Completed: _____ Stock Type SYN
 Engagement at Start (1) .0203 (2) .0204 (3) .0203 Average .0203
 Engagement at End (1) .0201 (2) .0200 (3) .0199 Average .0200
 Model No. M/710 Serial No. 71126321
 Trigger Pull at Start of Test (1) 4.061 (2) 4.210 (3) 4.184 (4) 3.952 (5) 3.976
 Average Trigger Pull at Start of Test: 4.077 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 3.405 (2) 3.682 (3) 3.641 (4) 3.555 (5) 3.377
 Average Trigger Pull at End of Test: 3.532 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/BL

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI/SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the **unlocked**
 position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>	<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/BL

Page 1 of 3
 Z101NDROPTTEST_REV5.DOC

ET22585