

RIFLE # A-1
S.N. 71163360
CAL. 30 - 06 SPRG

M/710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START -		TOTAL RDS.
				RDS. FIRED		
Blee	7-12-04	Initial Headspace	min + .002	TLW1530 B		
Blee	7-13-04	ProoF	0	TLW1530 C	1	1
Blee	7-13-04	Re-measure Headspace	min + .002	TLW1530 D		
Blee	7-13-04	Indents	.026 .020 .019 Avg. .0196	TLW1530 E		
SW	7-14-04	Engagement	See Data Sheet	TLW1530 F		
SW	7-15-04	Sew/Firing Pin Head Engagement	See Data Sheet	TLW1530 G		
SW	7-15-04	Trigger Pull	See Data Sheet	TLW1530 H		
QL	7-16-04	5 m/s ON/OFF Forces	See Data Sheet	TLW1530 I		
QL	7-16-04	Bolt opening and closing forces	See Data Sheet	TLW1530 J		
SW	7-16-04	Searc Lift	See Data Sheet	TLW1530 F		
DL	8-5-04	200rd Basic Jack Function Test	1 SL	TLW1530 N	80	81
JS	8-10-04	(Receiver Modified)	Machined chamber to aid in feeding ammo	TLW1530 M	120	201
BL	8-12-04	200rd Basic Jack Function Test		TLW1530 O	20	221
SW/JS	8-12-04	Shoulder Function Test	0 Malfunction		20	241
BL/JS	8-12-04	Accuracy				
SW	8-16-04	Clean & Inspect	OK Headspace min + .004	TLW1530 Y		
SW/JS	8-30-04	Semi Juv - Off	Pass	TLW1530 Z		
SW/JS	8-31-04	Semi Rotation	Pass	TLW1530 AA		
SW/JS	8-31-04	Semi Drop	Pass	TLW1530 AB		
SW/JS	9-2-04	Extended Juv - Off	18" Pass	TLW1530 AD		
SW/JS	9-2-04	Extended Juv - Off	24" Failed			
SW	9-8-04	Put insert into	A-13			
			Broken Insert from A-13 into			
			A-1			

83

DAILY DATA SHEET

Remington Arms Confidential

Page 1

ET22738