

G-6300481

VERY IMPORTANT
INSTRUCTION BOOK
ENCLOSED TO ASSURE
SAFE USE OF THIS
RIFLE

Remington®

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

Made in Illinois, NY Reg. U.S. Pat. & Tm. Off. Marca Registrada Torque Deposited

SERIAL NO. **J**
G6300481

ORDER NO.
25716

08KX

46

5716 G6300481

ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYST
UPC



ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYST
UPC



SERIAL NO.




M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

46 FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6300481

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # C6300481

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		3-21-03	RTL
600	PROOF		3-21-03	RTL
607	CHECK HEADSPACE	MAGNA-FLUX INSPECTED	3-21-03	RTL
610	DIS-ASSEMBLE GUN		3-21-03	RTL
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	MAR 25 2003 OPERATOR <i>ABX</i>		
615	ROLLMARK CALIBER		3/27/03	B
617	DRILL AND TAP SIGHT HOLES		3-25-03	TRW
620	APPLY COATINGS (BARREL ACTION)		4-3	TA
	(BOLT)		4-3	TA
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY		4/4/03	RA
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		4/4/03	RA
	C) INSPECT EJECTOR HOLE FOR CHAMFER		4/4/03	RA
	D) OIL FIRING PIN ASSEMBLY		4/4/03	RA
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS		5-2-03	TRW

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>6.0</u> <u>6.5</u> <u>6.5</u>	5-2-03	TRW
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>2.0</u> <u>2.5</u> <u>2.5</u>	5-2-03	TRW
	H) TRIGGER PULL TEST AND RETAINABILITY		5-2-03	RTL
	I) FIRING PIN INDENT .020 MIN	<u>.023⁵</u> <u>.022⁵</u> <u>.023</u>	5-2-03	TRW
	J) ASSEMBLE STOCK		04-07-03	RTL
	K) ASSEMBLE SWIVEL STUDS		5-6-03	RTL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		5-6-03	RTL
	M) IRON SIGHT ALIGNMENT		5-6-03	RTL
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		5-6-03	RTL
640	GALLERY TEST AND TARGET	PASS FAIL	4-16-03	TRW
	MALFUNCTION	CORRECTION	4-16-03	TRW
	MALFUNCTION	CORRECTION	4-16-03	TRW
	MALFUNCTION	CORRECTION	4-16-03	TRW
	MALFUNCTION	CORRECTION	4-16-03	TRW
645	INSPECT FOR LIVE AMMO		4-16-03	TRW
655	FINAL INSPECTION A) HEADSPACE		5-6-03	RTL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.38</u> <u>2.48</u> <u>2.50</u> <u>2.40</u> <u>2.40</u>	5-2-03	TRW
	C) FUNCTION		5-6-03	RTL
660	PACK		5/6/03	RTA

AVERAGE PULL FORCE BETWEEN

SERIAL NO.

BARBER - M24 0161050

2.50# ± .50#

DATE 12-4-02

3.00# ± .75#

TESTER TRW

4.00# ± 1.00#

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.52	2.51		2.38	MIN. SETTING
PULL #2	2.44	2.46		2.30	NO AVG. OF 5
PULL #3	2.45	2.42		2.13	READINGS ACCEPT
PULL #4	2.52	2.35		2.11	ABLE LESS THAN
PULL #5	2.72	2.39		2.13	
TOTAL	12.65	12.13		11.05	
AVG.	2.53	2.42		2.21	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.27	3.31		
PULL #2	3.23	3.23		
PULL #3	3.31	3.29		
PULL #4	3.39	3.14		
PULL #5	3.20	3.22		
TOTAL	16.40	16.19		
AVG.	3.28	3.23		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# TARGET & ACCU
PULL #1	4.16	4.00		4.05
PULL #2	4.06	4.03		4.16
PULL #3	4.11	4.17		4.15
PULL #4	4.05	4.20		4.13
PULL #5	4.09	4.09	1.1	4.10
TOTAL	20.47	20.49		20.59
AVG.	4.09	4.09		4.11

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6300481.___0
FILE DATE AND TIME: 04/18/2003 00:34

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES


ERROR - NOT POSSIBLE TO REPORT SWS STATS ON DATA
WHERE TOTAL TARGETS ARE NOT EQUAL TO FIVE

Ave mean .796

SERIAL NUMBER: G6300481. 0
 TARGET NUMBER: 1
 FILE DATE: 04/18/2003
 FILE TIME: 00:34

POINT#	X	Y
1:	1.131	-0.897
2:	-0.031	-0.599
3:	0.505	0.045
4:	-0.078	0.451
5:	-0.498	0.421

X CENTROID: 0.206
 Y CENTROID: -0.116
 POA TO CENTROID: 0.236
 HORZ SPREAD: 1.629
 VERT SPREAD: 1.348
 GROUP SPREAD: 2.095
 MIN RADIUS: 0.340
 MAX RADIUS: 1.211
 MEAN RADIUS: 0.722
 # IN 1 IN DIAMETER: 1
 # IN 2 IN DIAMETER: 4
 # in 3 IN DIAMETER: 5




TARGET APPROX 1/2 SCALE

BARBER - M24 0161053

SERIAL NUMBER: G6300481. __0
 TARGET NUMBER: 2
 FILE DATE: 04/18/2003
 FILE TIME: 00:34

POINT#	X	Y
1:	0.883	-0.026
2:	0.314	-0.065
3:	-0.199	-0.902
4:	-1.082	-0.125
5:	-0.329	1.039

X CENTROID: -0.083
 Y CENTROID: -0.016
 POA TO CENTROID: 0.084
 HORZ SPREAD: 1.965
 VERT SPREAD: 1.941
 GROUP SPREAD: 1.945
 MIN RADIUS: 0.400
 MAX RADIUS: 1.083
 MEAN RADIUS: 0.870
 # IN 1 IN DIAMETER: 1
 # IN 2 IN DIAMETER: 3
 # in 3 IN DIAMETER: 5



TARGET APPROX 1/2 SCALE