

RIFLE # A-2
S.N. 71163358
CAL. 30 - 06 SPRG

M / 710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED	TOTAL RDS
B.Lee	7-12-04	Initial Headspace	min +.002 TLW1530B		
B.Lee	7-13-04	Proof	OK TLW1530C	1	1
B.Lee	7-13-04	Re-measure Headspace	min +.002 TLW1530D		
B.Lee	7-13-04	Indents	.019 - .019 - .018 Avg. .0186 TLW1530E		
SW	7-14-04	Engagement	See data sheet TLW1530F		
SW	7-15-04	Sear/Firing Pin Head Engagement	See data sheet TLW1530G		
SW	7-15-04	Trigger Pull	See data sheet TLW1530H		
BL	7-15-04	Safety ON/OFF forces	See data sheet TLW1530I		
BL	7-15-04	Bolt opening/closing forces	See data sheet TLW1530J		
SW	7-16-04	Sear Lift	See data sheet TLW1530F		
BL	8-5-04	200 Rd Basic Jack Function Test	TLW1530N	80	81
JS	8-10-04	(Receiver Modified) — Machine chamber to aid in Feeding ammo			
BL	8-12-04	200 Rd Basic Jack Function Test	TLW1530N	120	201
SW/MH	8/12/04	Shoulder Function Test 0 Malfunction	TLW1530O	20	221
BL/JS	8/12/04	Accuracy		20	241
SW	8/16/04	Clean & Inspect	OK Headspace Min +.003 TLW1530R		
JS	8/24/04	Endurance Test	OK TLW1530Q	500	741
SW	8/30/04	Clean & Inspect	OK Headspace Min +.003 TLW1530P		
SW/JW	8/30/04	Szumi Juv-OFF	Pass TLW1530Y		
SW/JW	8/31/04	Szumi Rotation	Pass TLW1530Z		
SW/JW	8-31-04	Szumi Drop	Pass TLW1530AA		
SW/JW	9-2-04	Extended Juv-OFF	18" Pass TLW1530AB		
SW/JS	9-2-04	Extended Juv-OFF	24" Pass TLW1530AB		
SW/JW	9-2-04	Extended Juv-OFF	36" Failed TLW1530AD		
SW	9/8/04	Put insert into A-14	Broken Insert from A-14 into A-2		

DAILY DATA SHEET

Remington Arms Confidential

Page 1

BARBER - 5.22.06P0005750

Confidential - SHARBER - 5.22.06P0005750 Order

ET22750

Williams v. Remington