

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 EXTRUDED RECEIVER

Project: 241230

Rifle: A-3

TLW #: TLW1530

Date: 8 / 30 / 04Inspector: S WRound Level: 741

- ☒ Measure Headspace Min +.003
- ☒ Sear Engagement: 1st .0264 2nd .0263 3rd .0263 Ave. .02633 spec. .020" to .025" 83
- ☐ Reset Sear Engagement if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____
- ☒ Trigger Pull: 1st 5.095 2nd 5.119 3rd 5.032 Ave. 5.079 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear, bolt stop little wear
- ☒ Inspect stock for any signs of cracking or other failure. OK
- ☒ Other items of note: _____
- _____
- _____
- _____

TLW1216

Remington Confidential

ET22778