

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 EXTRUDED RECEIVER

Project: 241230

Rifle: A-4

TLW #: TLW1530

Date: 8 / 16 / 04Inspector: SW

Round Level: _____

- ☒ Measure Headspace Min 4.004
- ☒ Sear Engagement: 1st. .0269 2nd. .0271 3rd. .0268 Ave. .02693 spec. .020" to .025" 83
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 4.493 2nd. 4.392 3rd. 4.508 Ave. 4.464 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs normal wear
- ☒ Inspect stock for any signs of cracking or other failure. OK
- ☐ Other items of note: _____
- _____
- _____
- _____

TLW1216

Remington Confidential

ET22802