

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 EXTRUDED RECEIVER

Project: 241230

Rifle: A-4

TLW #: TLW1530

Date: 9 / 1 / 04Inspector: SWRound Level: 1221

- ☒ Measure Headspace Mint + .004
- ☒ Sear Engagement: 1st. .0280 2nd. .0276 3rd. .0281 Ave. .0279 spec. .020" to .025"
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 4.488 2nd. 4.585 3rd. 4.508 Ave. 4.537 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs normal wear, bolt stop little wear,
- ☒ Inspect stock for any signs of cracking or other failure. OK
- ☒ Other items of note: _____
- _____
- _____
- _____

TLW1216

Remington Confidential

ET22814