

RIFLE # A-5  
S.N. 71163350  
CAL. .270 WIN

M / 710 EXTRUDED RECEIVER D.A.T.

PROJECT: #  
TLW: # 1530

| NAME  | DATE    | TEST ACTIVITY                        | COMMENTS                                | ROUNDS AT START. |            |
|-------|---------|--------------------------------------|-----------------------------------------|------------------|------------|
|       |         |                                      |                                         | RDS. FIRED       | TOTAL RDS. |
| B Lee | 7-12-04 | Initial Headspace                    | min 1.002                               | TLW1530B         |            |
| B Lee | 7-13-04 | PROOF                                | OK                                      | TLW1530C         | 1          |
| B Lee | 7-13-04 | Re-measure Headspace                 | min 1.002                               | TLW1530D         |            |
| B Lee | 7-13-04 | Indents                              | .020 - .019 - .020 Avg. .0196           | TLW1530E         |            |
| SW    | 7-14-04 | Engagement                           | See data sheet                          | TLW1530F         |            |
| SW    | 7-15-04 | Sear / Firing Pin Head Engagement    | See data sheet                          | TLW1530G         |            |
| SW    | 7-15-04 | Trigger Pull                         | See data sheet                          | TLW1530H         |            |
| B.L   | 7-15-04 | Safety ON/OFF Forces                 | See data sheet                          | TLW1530I         |            |
| BL    | 7-15-04 | Bolt opening / closing Forces        | See data sheet                          | TLW1530J         |            |
| SW    | 7-16-04 | Sear Lift                            | See data sheet                          | TLW1530F         |            |
| SW    | 7/22/04 | 200 Rd Basic Jack Function Test      | OK                                      | TLW1530N         | 200        |
| SW/PR | 7/26/04 | 20 Rd Shoulder Function Test         | OK                                      | TLW1530O         | 20         |
| JK    | 7/26/04 | Accuracy Testing                     |                                         | TLW1530P         | 20         |
| SW    | 7/27/04 | Cleaned & Inspected                  | OK                                      | TLW1530R         |            |
| BL    | 7/29/04 | Extended function & Endurance test   |                                         | TLW1530Q         | 500        |
| BL    | 7/29/04 | Cleaned & Inspected                  | OK                                      | TLW1530R         |            |
| BL    | 7/30/04 | Extended function & Endurance test   | 5 FTE                                   | TLW1530Q         | 500        |
| BL    | 8/2/04  | Clean & Inspected                    | OK                                      | TLW1530R         |            |
| BL    | 8/3/04  | Hot Function Test                    | OK                                      |                  | 100        |
| JS    | 8/10/04 | Receiver Modified                    | Machined chamber to add in feeding ammo |                  | 1341       |
| B Lee | 8-12-04 | Jack Function Test Additional rounds | OK                                      | TLW1530N         | 200        |
| SW    | 8/16/04 | Cleaned                              |                                         |                  |            |
| SW    | 9/1/04  | Took insert and put in A-10          |                                         |                  |            |

DAILY DATA SHEET

Remington Arms Confidential

Page 1

BARBER - 5.22.06r0005821

Confidential - Sparker .502206r0005821 Order  
Williams v. Remington

ET22821