

TLW 141620

Project No. 241314

20.06

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**JAR-OFF TEST**

Firecontrol No. A-5 Firecontrol Type: Standard Date: 6/5/04
 Dry Cycles/Rounds Completed: _____ Stock Type Syn
 Engagement at Start (1) .0242 (2) .0241 (3) .0241 Average .02413
 Engagement at End (1) .0240 (2) .0241 (3) .0241 Average .02406
 Model No. 710 Serial No. 71159114
 Trigger Pull at Start of Test (1) 4.625 (2) 4.499 (3) 4.402 (4) 4.504 (5) 4.523
 Average Trigger Pull at Start of Test: 4.511 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.523 (2) 4.422 (3) 4.586 (4) 4.579 (5) 4.485
 Average Trigger Pull at End of Test: 4.519 Std. Dev. of Trigger Pull at End of Test: _____
 Tester Initials: SW/JS
 Additional Notes and Comments _____

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI/SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>	<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/JS

Page 1 of 3
 Z101\DROPTEST_REV5.DOC

ET23285

TLW 1463E

Project No. 241214

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**ROTATION TEST**

Firecontrol No. A-5 Firecontrol Type: _____ Date: 6/6/04
 Dry Cycles/Rounds Completed: _____ Stock Type _____
 Engagement at Start (1) .0242 (2) .0241 (3) .0241 Average .02406
 Engagement at End (1) .0263 (2) .0261 (3) .0263 Average .02623
 Model No. _____ Serial No. _____
 Trigger Pull at Start of Test (1) 4.523 (2) 4.422 (3) 4.586 (4) 4.579 (5) 4.485
 Average Trigger Pull at Start of Test: 4.519 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.594 (2) 4.588 (3) 4.650 (4) 4.669 (5) 4.483
 Average Trigger Pull at End of Test: 4.597 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SL/JS

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials SL/JS

Page 2 of 3
 Z101IDROPTTEST_REV5.DOC

ET23286

TLW 1463F

Project No. 121314

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**DROP TEST**Firecontrol No. A-5 Firecontrol Type: _____ Date: 6-6-04

Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start _____

Engagement at Start (1) .0242 (2) .0242 (3) .0242 Average .02430Engagement at End (1) .0245 (2) .0243 (3) .0243 Average .02436

Model No. _____ Serial No. _____ Engagement at End _____

Trigger Pull at Start of Test (1) 4.441 (2) 4.555 (3) 4.697 (4) 4.579 (5) 4.580Average Trigger Pull at Start of Test: 4.570 Std. Dev. of Trigger Pull at Start of Test: _____Trigger Pull at End of Test (1) 4.734 (2) 4.774 (3) 4.707 (4) 4.670 (5) 4.722Average Trigger Pull at End of Test: 4.721 Std. Dev. of Trigger Pull at End of Test: _____Tester Initials: SW/JW

Additional Notes and Comments

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI/SAAMI Z299.5-1990

SAAMI Specifications for Standard Drop Test:

Drop Test: 48 inch drop onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

*Note: for Firearms with the ISS system installed - The Firearms will be set with the**ISS system in the unlocked position for all six orientations of the Drop Test*

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	<u>bent scope</u>
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/JW

Page 3 of 3

Z101\DROPTEST_REV5.DOC

ET23287