

Original 9/13/54

REVISED 6/6/55 4-16-58

REMINGTON STANDARDS - ARMS

SHEET 2

MODEL 40X RANGEMASTER		S-2 Std. Bbl.	H-2 Heavy Bbl.	S-1 (With Sights)	H-1 (With Sights)
BARREL					
Length	28" tolerance $\pm 1/16"$ measured from face of locked bolt.				
Shape	Round, tapered				
Muzzle	No crown, counter sink				
Finish	Black, medium lustre; Browning, minimum 2 coats.				
Material	High strength, steel alloy				
Rifling	6 grooves, 1 turn in 16" RH				
Bore Diameter	.2177" min.; .2182" max.				
Groove Diameter	.2217" min.; .2222" max.				
Groove Width	.087" min.; .089" max.				
NOTE:	No constriction in bore or groove shall exceed .0002"				
Chamber	22 long rifle only - Special design for match shooting.				
Scope Mounts	Target type (see SCOPE MOUNTS)				
Sights	(Redfield Olympic) See SIGHTS (front plug screws (2) provided)				
Weight	light			light	heavy
Bedding	adjustable (see STOCK)				
BOLT					
Locking Lugs	Locking lugs (2) Front section of Bolt Plug.				
Extractors	Top; horizontally opposed				
Finish	Bolt head - Bright Remainder of bolt assembly - Black				
	Bolt Handle - Slight sweepback				
BOLT STOP RELEASE					
	Located at head of trigger (on trigger housing assembly)				
BUTT PLATE					
	Non slip; hard rubber base, white line, thin soft rubber pad, grooved				
GUN LENGTH					
	46-3/4" overall				

BARBER - PRESALE R 0101392

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

BARBER - PRESALE R 0101392
R2502380