

M/600 - Cal. 6MM

Pilot Line Test

4/24/64

Gun Serial No.	Headspace		Ammuni- tion	Rounds	No. Malfr.	Type of Malfunction	Trigger Pull (lbs.)			Accuracy (Inches)						
	Go	No Go					Avg. of 10	Max.	Min.	Shoulder 5-Shot Group				Firing Pin Indent		
										1	2	3	Avg.	Min.	Max.	Avg. 5
10068	OK	OK	Rem. 100gr. PSP	20	-	Test #1 #2	5.475 5.5	6.0 6.5	5.0 5.25	1.95	1.6	1.92	1.82	.015	.0165	.0157
10144	OK	OK	"	20	-	Test #1 #2	6.275 6.3	7.75 6.75	5.5 5.75	1.9	2.1	1.4	1.80	.016	.0175	.0168
10061	OK	OK	"	20	-	Test #1 #2	4.725 4.3	5.75 4.5	4.25 4.0	2.05	2.1	2.15	2.1	.014	.015	.0147
10135	OK	OK	"	20	-	Test #1 #2	5.2 5.4	5.75 5.75	5.0 5.0	2.35	1.7	2.15	2.1	.016	.018	.0169
10164	OK	OK	"	20	-	Test #1 #2	7.45 6.3	9.25 7.0	6.5 5.75	2.25	2.25	1.3	1.93	.0155	.017	.0162
10133	OK	Closes on max. Plug (snug)	"	20	-	Test #1 #2	5.95 5.6	6.5 6.00	5.5 5.3	1.9	2.0	2.0	1.96	.0155	.018	.0166
10143	OK	OK	"	20	-	Test #1 #2	5.15 5.4	5.75 6.25	4.75 4.75	1.75	1.5	2.15	1.80	.016	.017	.0167
10148	OK	OK	"	20	-	Test #1 #2	6.8 6.03	7.75 6.5	6.25 5.5	2.0	2.75	2.3	2.35	.0165	.018	.017
10141	OK	OK	"	20	-	Test #1 #2	7.125 6.125	9.0 7.25	5.75 5.25	1.65	2.3	1.6	1.85	.016	.017	.0165
10170	OK	OK	"	20	-	Test #1	6.075 5.6	6.75 6.00	5.25 5.25	1.3	1.85	1.5	1.55	.015	.0175	.0164

BARBER - PRESALE R 0102580

BARBER - PRESALE R 0102580

R2503568