

NOV-23-94 WED 12:00

11/23/94

12:25

REMINGTON EXEC OFFICE

DONALD HUNTLEY - 3029938855

FAX NO. 3029938855

P.03

NO. 153

United States Patent Office

3,255,545

Patented June 14, 1966

3,255,545
DROP FIRE PREVENTION MECHANISM
 Raymond L. Chambers and Wayne F. Lusk, both of Elms, N.Y., assignors to Remington Arms Company, Inc., Bridgeport, Conn., a corporation of Delaware
 Filed May 4, 1964, Ser. No. 364,293
 4 Claims. (Cl. 43-70)

This invention relates to a device to prevent discharge of a firearm due to its being dropped and in particular to an inertia weight in the fire control mechanism to prevent the firearm from firing off when dropped on the muzzle.

Normally, firearms have the trigger positioned adjacent the rear and usually directly connected to a rear block or equivalent member. Such a structure is inherently stable and not susceptible to jar-off if properly made. The addition of weight to such a structure, will, however in some instances cause the firearm to jar-off when dropped.

The addition of weight in a fire control system usually centers where it is necessary to position a trigger receiver from the rest of the system. The simple addition of a link between a trigger and rear block or like member adds enough weight to sometimes cause jar-off if the firearm is dropped. If the link is arranged to move forward due to trigger pull, the inertia of this member will cause it to move forward when the firearm is dropped causing the trigger to move forward and consequently cause the firearm to fire. In such an arrangement the firearm will not fire when dropped butt down. When such a system is used, means are provided in the fire control mechanism to prevent so-called drop firing.

It is therefore the main object of this invention to provide an inertia weight in a fire control mechanism to prevent accidental firing of a firearm.

A further object of this invention is to prevent drop firing of a firearm.

Still another object of this invention is to prevent drop firing of a firearm by means of a trigger balance.

It is contemplated that these objectives may best be achieved by providing an inertia weight to function to prevent jar-off when the firearm is dropped. The inertia weight is called a trigger balance and is mounted in the rear immediately the end of a trigger link which joins the trigger and rear block. The balance is spring biased to maintain contact with the link and is freely pivotable in the rear.

It should be understood that the embodiments of the invention to be disclosed are equally applicable to all firearms having the trigger positioned remote from the rest of the fire control mechanism whereby a connecting member is required between the trigger and remainder of the fire control mechanism.

Other objects and advantages of this invention will become apparent as the following description proceeds, and the features of novelty which characterize this invention will be pointed out with particularity in the claims appended to and forming part of this specification.

In the drawings:

FIGURE 1 is a fragmentary sectional side elevation of a firearm incorporating this invention;

FIGURE 2 is a fragmentary sectional view looking down on the trigger link and trigger balance forming a part of this invention; and

FIGURE 3 is a perspective view of the trigger balance and a portion of the trigger link forming a part of this invention.

The drawings illustrate a bolt action handgun comprising a receiver 1 mounted on a stock 3 and having a barrel 3 secured in one end. The handgun is of the

ball-action type and may more readily be referred to as a bolt-action pistol. A bolt 4 is mounted in receiver 1 for reciprocation to and from the battery or firing position. Bolt 1 is reciprocated manually by bolt handle 5 partially shown in FIG. 1.

The fire-control mechanism 6 includes a trigger 7, a member or trigger link 8 and a rear block 9. A safety 10 is mounted for pivotal movement on pin 11. Trigger 7 is pivotally mounted on trigger pin 12 and has link 8 pivotally attached thereto by pin 13. The remainder of the fire-control mechanism is of the conventional type for bolt action firearms. While this structure is not shown, it is to be understood that a firing pin is contained in bolt 4 and arranged to be cocked upon rotation and reciprocation of the bolt. The pin is held in the cocked position by the rear which in turn is held by rear block 9. Movement of block 9 releases the rear and firing pin allowing the gun to fire.

Receiver 1 is secured to stock 3 by means of screw 14 and another screw not shown which passes through receiver 1 and screws into block 15 positioned in stock 3. Barrel 3 is attached to receiver 1 but not to stock 3 in any manner so it is a free floating barrel. Stock 3 is preferably molded from nylon but can be made of wood or any other material suitable for pistol stocks. A rib 16 is mounted on barrel 3 and the sights are mounted on rib 16. The front sight is not shown but rear sight 17 can be seen mounted on rib 16.

It can clearly be seen in FIG. 1 that the pistol shown has trigger 7 positioned quite a distance from fire control 6. In order for the gun to fire, squeezing trigger 7 must actuate the fire control to cause discharge of a cartridge loaded in the chamber which is within receiver 1. In the particular gun shown, rear block 9 must be moved in response to a squeeze on trigger 7. This movement is accomplished by connecting trigger 7 to rear block 9 by trigger link 8. The added weight of link 8, however, causes difficulties occurring jar-off or firing when the gun is dropped.

Rear block 9 is designed to move forward or toward trigger 7 when trigger 7 is squeezed. This is toward the muzzle end of the pistol. For ease of description the opposite end will be called the butt end. When dropped on the butt end the firearm will not fire or discharge. When firearm discharges as a result of being dropped they are considered to jar-off as a result of the drop. Rear block 9 must move forward before the pistol can fire and dropping on the butt end will not cause this type of movement. When dropped on the muzzle, however, the inertia of link 8 causes it to move forward pulling rear block 9 with it and causing the pistol to fire or jar-off.

In order to prevent jar-off due to dropping, the firearm is provided with an inertia weight or trigger balance 18. Balance 18 is formed with two oppositely extending arms 19 mounted on a thin upright section 20. Arms 19 are mounted in groove 21 in stock 3 and are positioned intermediate the ends of link 8. Link 8 is formed with elongated openings 22 and 23 for screw 14 and block 15 as well as opening 24 through which section 20 passes. A trigger balance spring 25 is mounted on arms 19 and biases section 20 of balance 18 toward link 8 except when the pistol is dropped on the butt end.

When the gun is dropped on the muzzle and the inertia of balance 18 forces section 20 against link 8 preventing forward movement by link 8. Normal firing is not impeded by balance 18 because it is freely pivoted in stock 3 and spring 25 is very light. A pull or squeeze on trigger 7 causes a balance 18 to pivot on arms 19 allowing forward movement of link 8 and the consequent firing of the pistol.

11/23/94

WASHINGTON EXEC OFFICE

5

3.2

09-06-2008

15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850

三	三
三	三
三	三
三	三

Indigenous Owned by the Government	
UNITED STATES PATENTS	
1,112,012	1/1/17
1,177,331	2/1/17
1,245,716	1/1/17
FOREIGN PATENTS	

Not a claim for

134,304 18/1911 Germany.

**Indigones Owned by the Boarding
UNITED STATES PATENTS**

UNITED STATES PATENTS

1/1917	Belgium	42-71
2/1943	East Prussia	43-71
1/1957	Nagano	42-71
2/205,765		
2/272,204		
1/312,012		

POULSON PATENT

400,777 2/19/10 Presk.
234,304 10/19/11 Germany.

IRVING A. ROBERTS, Deputy Inspector