

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Gun
 Firecontrol No. B25 Firecontrol Type: Standard Date: 12/4/00
 Dry Cycles/Rounds Completed: _____ Stock Type Syn Engagement at Start _____
 Model No. 710 Serial No. 71001643 Engagement at End _____
 Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW

Additional Notes and Comments

New angle connector

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____