

BARBER PRESALE R 0103382

REMINGTON STANDARDS - ARMS

MODEL	600	308 Win.	6MM Rem.	222 Rem.	243 Win.	243 Win.	223 Rem. (Export only)
ACCURACY							
Range	100 yards						
Point of Aim	6 o'clock on target.						
Center of Impact	Not more than 2 inches	below or 4 inches above or 3 inches either side of point of aim.					
Group Size (E.S.)	5 shots in:	3 1/2"	2 1/2"	2 1/2"	XXXX	2 1/2"	2 1/2"
	4 shots in:	3"			XX		
Ammunition		180 gr. PSP	100 gr. PSP	50 gr. SP	XXXXXX	100 gr. PSP	55 gr. SP
ACTION							
	Bolt action, hand operated. Removable bolt. Solid frame with takedown stock. Bolt cocks as handle is raised. Rifle cocks as bolt handle is lowered to lock action closed. Extracts and ejects as bolt is "opened". Direct action trigger. 2 stop safety - Forward to FIRE position - rearward to ON SAFE stop position.						
	Action must feed, fire, extract and eject (include extraction and ejection without firing) satisfactorily with all varieties of ammunition listed as standard (for tabulated calibers) in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).						
ANNOUNCEMENT							
Jan.		1964		1964	1964	1965	
June			1964				1965
Warehouse Date							
DISCONTINUED							
Jan.					1967		
June							

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

BARBER - PRESALE R 0103382

R2504370

SHEET 2

REMINGTON STANDARDS - ARMS

REVISED 4-1-66 3-22-67

MODEL 600	308 Win.	6MM Rem.	222 Rem.	243 Win.	223 Rem. (Export only)
BARREL	Round tapered to breech and crowned at muzzle. Black color, medium lustre. Remington specification alloy steel. Steel barrel studs (6) for rib and sight attachment.				
Bedding	No requirement.				
Barrel Bracket	Elevated type.				
Length (Nominal)	18 1/2"				
Diameter (O.D.)	Regular size.				
Bore (in.)	.300 min.	.237 min.	.219 min.	.237 min.	.219 min.
	.302 max.	.238 max.	.220 max.	.238 max.	.220 max.
Groove (in.) (6)	.308 min.	.243 min.	.2240 min.	.243 min.	.224 min.
	.310 max.	.244 max.	.2250 max.	.244 max.	.225 max.
Twist (R.H.)					
1 Turn in	10 inches	9 inches	14 inches	9 inches	12 inches
Markings	See MARKINGS - Barrel				
BARREL RIB	Black Delrin. Ventilated type attached to barrel studs with screws. Matted between sight positions.				
BOLT (Final Assembly)	Includes Bolt Assembly, Firing Pin Assembly.				
Bolt Body	Bright steel				
Bolt Plug	Black color.				
Bolt Handle	Bright steel color. Forward "S" shape with oval "half ball". Serrated on bottom of half ball.				
Firing Pin Head	Black color.				
Markings	Serial number on bottom of bolt. See MARKINGS - Bolt.				
Export	Use "shrouded" bolt plug - special design.				
BOLT STOP	Located in left rear of "bolt track" in receiver. Use narrow tool to push down for release.				

BARBER - PRESALE R 0103384

REMINGTON STANDARDS - ARMS

SHEET 3

MODEL 600		308 Win.	6MM Rem.	222 Rem.	XXXXXX	243 Win.	223 Rem.
		(Export only)					
BUTT PLATE	Black plastic						
EJECTOR	Plunger type - spring loaded and pin assembled in bolt head.						
EXTRACTOR	Riveted to bolt.						
PRING PIN	Spring retracted in bolt.						
Protrusion	.045 min. - .075 max.						
Indent	.018 min. - .026 max. (using copper crusher)						
GUN - Length (Overall)	37 1/4" (Nominal)						
- Weight	5 1/2 lbs. (Nominal)						
MAGAZINE	Fixed - top loading						
Capacity	4	4	5	XX	4	5	
Follower	Bright plate.						
Spacer	No	No	Yes	XXX	No	Yes	
</							

BARBER - PRESALE R 0103384

REVISED 18-26-66:

3-22-68

REMINGTON STANDARDS - ARMS

SHEET 4

MODEL	600	308 Win.	6MM Rem.	222 Rem.	X360REM.	243 Win.	223 Rem. (Export only)
MARKINGS	All marking visible unless specified otherwise.						
Barrel	Dwg. B-15729						
Assembly	Left rear						
Remington Name	Left side						
Rem. Address	Left side						
Caliber	Left rear						
Code (Mfg. Date)	Left rear						
Patent Numbers	Below Remington name (if any)						
Proof (REP)	Right rear						
Test	Right rear						
Other:							
Magneflux	Right rear (to rear of (REP) marking).						
Receiver	Dwg. B-15482)						
Grade	None						
Remington Script	Left center						
Model Number	Below script (Rem.)						
Serial Number	Left front						
Export:	To Australia: Mark "S" and "P" on receiver adjacent to respective SAFE and FIRE stop positions of safety.						
Bolt	(Prick-punch mark) Ref. Current practice.						
Magneflux	Right lug (center)						
Bolt head braze	Left lug (center)						
Bolt handle braze	Rear handle (center)						
Proof	Bottom handle (center)						
METAL FINISH	Black color, medium lustre on all exposed parts except as otherwise tabulated.						
PATENT NUMBERS	None						

SHEET 5

REMINGTON STANDARDS . ARMS

REVISED 3-22-67 7-1-65

MODEL 600	308 Win.	6MM Rem.	222 Rem.	XXXXXX	243 Win.	223 Rem.
PACKAGING	Full length.	Exposed metal parts coated with rust preventive.			Bolt in rifle.	(Export only)
Accessories	Rear sight wrench supplied.					
Literature	Instruction Folder - Parts List RD 5473					
Single Shipper	Single piece corrugated sheet, integral folds for rifle support. black artwork (Deer and Bear). Lid taped to close.				Marbled color with brown and	
Multiple Shipper	Sleeve or full carton of corrugated material.					
Label	Green and white, model, serial number, caliber, packers code on label.					
Markings	Name and address of addressee, with copy of shipping ticket, return address.					
Shipping Weight						
1 Gun	8 lbs.					
2 Guns	16 lbs.					
3 Guns	23 lbs.					
5 Guns	38 lbs.					
Export	Same as domestic except	Legal or actual weight on label.				
PROOF TEST (REP)	Fire one (1) standard proof cartridge in each gun.				For location of marking (REP) see MARKINGS - Bar	
RECEIVER	Cylindrical alloy steel, black color, medium lustr.				Screw fitted to barrel and barrel bracket (solid frame).	
Sighting	Drilled and tapped (5 holes) for receiver sight and telescope mount.				Fitted with receiver plug screw	
Gas Escape	One (1) hole - right side.					
Length	Standard					
Markings	See MARKINGS - Receiver.					

BARBER - PRESALE R 0103386

R2504374
386

REVISED 11-20-65

8-22-67

REMINGTON STANDARDS - ARMS

SHEET 6

MODEL 600	308 Win.	6MM Rem.	222 Rem.	243 Win.	223 Rem. (Export only)
SAFETY	2-stop position, forward and back-thumb operated. Serrated black surface.				
Location	Right rear of receiver.				
Fire Position	Forward stop.				
Safe Position	Rear stop. (Bolt handle locks down - action closed).				
SERIAL NUMBER	(Start 1000)				
Location (1)	See MARKING - Receiver.				
(2)	See MARKING - Bolt.				
SLING STRAP	As accessory at extra cost.				
Description	7/8" QD type same as used on M/700. Leather material.				
SIGHTS	Metal material. Black color.				
Front	Fixed (no adjustment). Blade shaped ramp. Brass head. Attached on rib to barrel studs with two (2) screws.				
Rear	Sliding adjustment for windage and elevation.				
Eye-piece	Allen-head screw for elevation adjustment. "U" notch..				
Leaf	Allen-head screw for windage adjustment. Scaled markings.				
Base	Attached to barrel with two (2) screws.				
Wrench	Allen-head type. Supplied with each gun.				

RD-6488

SHEET 7

REMINGTON STANDARDS - ARMS

REVISED 11-20-65 3-22-67

[illegible]

附錄一

BARBER - PRESALE R 0103388

BARBER - PRESALE R 0103388

R2504376