

REMINGTON STANDARDS - ARMS

Rev. 1-14-80
REVISED 3-12-73

MODEL 700	1974 Version	ADL Grade	BDL Grade
STOCK (Continued)			
Dimensions (Nominal - 30-06		See Below	See ADL Grade
Drop at Heel (from $\bar{Q}$ of barrel)		1 5/16"	"
Drop at Comb & Monte Carlo (From $\bar{Q}$ of bbl.)		1 1/16"	"
Length of Pull		13 3/8"	"
Length of Grip		3 3/8"	"
Pitch (from $\bar{Q}$ of barrel)		2 7/8"	"
Fore-end Cap (black plastic)		No	Yes
Spacer (white plastic)		--	Yes
Grip Cap (black plastic)		No	Yes
Spacer (white plastic)		--	Yes
Swivels (2) 7/8" O. D. (Quick Detachable)		No	Yes
(1) Weight (7mm-08 Varmint)			2 lbs. - 7oz. Max.
TRIGGER	Direct action, black metal, wide serrated finger piece, full radius.		
Pull (Wt.)	3 lbs. Min. - 5 lbs. Max. (with wt. sealed at factory).		
Engagement	Adjustment sealed at factory.		
TRIGGER GUARD	Aluminum alloy, black color.	Anodized - High Lustre	
Type		Short	Long (with floor plate)
WEIGHT	(See Gun Length & Weight)		
(1) Added			

REVISED 3-12-73

SHEET 7 of 8

REMINGTON STANDARDS - ARMS

MODEL 700		1974 Version	ADL Grade		BDL Grade	
RECOIL PAD		Black Color				
Calibers:		All Magnum Grades only.				
(2) Markings:		"Remington" on back surface See Logo B2 for Size.				
Spacer		White Plastic				
SAFETY		2 stop position, thumb operated - forward and back. Corrugated, black surface.				
Location		Right rear of Receiver				
"FIRE" position		Forward stop position. Marked "F" on receiver.				
"SAFE" Position		Rearward stop position (Bolt lock position also). Marked "S" on receiver.				
SERIAL NUMBER		(Start 6,200,000 Last No. 6,899,999 Ref. See Marking Dwg. C-15360)				
Location		See MARKINGS - Receiver				
		See BOLT - Markings				
		(Last four (4) numbers only)				
SLING STRAP		Leather, one piece - purchased. Accessory			St. Equipment	
Type - 7/8"						
SLING SWIVEL 7/8"		See STOCK			Standard Equipment	
Q. P.						
SIGHTS		Metal, black color. (Removable).				
Front		Beas face held (dovetail) with screw (2) fill ramp.				
Rear (1)		Open, U-Notch - adjustable for windage and elevation. Sliding ramp for elevation				
STOCK (Assembly)		Anglolean walnut, reddish filler, Monte Carlo with cheek piece. Pistol grip with comb cuts and checkered (Custom). See action. Long action, short action caliber use RK-W				
Finish						
Rutt Plate		See Butt Plate				
Spacer (White Plastic)						
Recoil Pad		(MAGNUM caliber use only)				
Checking						
Recoil Pad Spacer (White Plastic)					D-91001	
(1) REF: On Comm. meeting		Min. No. 9, June 1972, approving release to production.				
(2) See Memo J. H. Lewis to J. F. Finnegan dated 8-24-73						

REMINGTON STANDARDS - ARMS

REVISÉD 3-12-73

MODEL 700 1974 Version		ADL Grade	BDL Grade
PACKING	Full length in single wall, inner rifle carton. Bolt removed and packed separately in same carton. Exposed metal parts coated with rust preventive.		
Inner Carton	One piece folding, corrugated fiberboard.		
Literature	Gun Owner's Guide - Form No. 5461 in carton. Misc. sale items if available.		
Markings	Printed label giving manufacturer, model name and/or number, caliber, serial number and packing code., sales number.		
Outer Carton	1, 2, 3 or 5 inner carton capacity. Corrugated carton of greater strength.		
Literature	Copy of regular Remington shipping ticket with, complete information.		
Markings	Name, address of Purchases with purchaser's order number.		
Shipping Weight			
1 gun	10 lbs.		
2 guns	19 lbs.		
3 guns	27 lbs.		
5 guns	46 lbs.		
Export	Packaging same as domestic but with "legal" or actual weight recorded on label.		
PATENT NO's.	2,473,373 -	2,514,981 -	2,585,195
PROOF TEST (REP)	Fire one (1 - standard proof cartridge in each rifle. For location of marking (REP), see MARKINGS - Barrel		
RECEIVER	Cylindrical, alloy steel, black medium luster.		
Action Lengths	See Gun Length and Weights		
Finish	Medium Luster.		
Gas Escape	(1) Right Hand Side		
Markings	See Markings - Receiver		
Sighting	(6 holes) Drilled and tapped for popular scope mount and receiver sight.		
Feature	Anti-bird design.		

REMINGTON STANDARDS - ARMS

REVISED 3-12-73

MODEL 700 1974 Version		ADL Grade	BDL Grade
MARKINGS - Barrel (Dwg. C-15360)			
Assembly	Left Rear		
Caliber	Left Rear of Remington name.		
Code (Mfg. Date)	Left Rear		
Inspection	Left Rear		
Patent Numbers	Below Remington address.		
Remington Address	Left Side		
Target	Right Rear.		
Test	Right Rear		
Magnaflux	Right Rear		
Other	---		
MARKINGS - Bolt (Prick-punch mark)			
Bolt Handle Braze	Rear Handle (Center)		
Bolt Head Braze	Left Lug (Center)		
Magnaflux	Right Lug (Center)		
Proof	Bottom Handle (Center)		
Serial Number (1)	Underside (Rear)	Last four (4) numbers only.	
MARKINGS - Receiver (Dwg. C-15360)			
Grade	None		
Model Number	Below Remington Script		
Model Script	None		
Remington Script	Left Side		
Serial Number	Left Side, Front		
Other	Mark "S" and "F" on receiver below and above resp. SAFE and FIRE stop positions of safety.		