

Competitive Product Evaluation
 Winchester Low-Priced Bolt Action
 Center Fire Rifles

LIMITED DISTRIBUTION

	<u>Remington 700ADL</u>	<u>Winchester 770</u>
ejection port length:	3.24"	3.11"
longitudinal primary extraction cam motion:	.08"	.15"
primary extraction cam surface:	visible, external on rear face of rear receiver ring	hidden, internal near rear face of rear receiver ring

Bolt

1. Consumer Oriented

bolt body:	polished and jeweled; black color left on front and rear portions	polished, not jeweled; color polished away from front and rear portions
bolt handle:	ellipsoidal-shaped knob, checkered top and bottom; black oxidized knob and handle; swept back to position knob over trigger	pear-shaped knob, smooth surface; highly polished and colored knob and handle; swept back to position knob over trigger
cross-sectional shape	primarily square	primarily round
(bolt plug, R): (bolt sleeve, W):	streamlined, no projections, black oxidized	less streamlined; houses safety, bolt sleeve lock, and firing pin retaining screw; polished and colored
cocking indicator:	flat rear face of firing pin head projects 3/64" beyond rear of bolt plug when cocked, provides visual and tactile indication	rear of firing pin sleeve projects 3/16" beyond rear of bolt sleeve when cocked, top of firing pin sleeve serrated and colored red, provides slightly better visual and tactile indication