

REVISED 5-9-72

REMINGTON STANDARDS - ARMS

SHEET 1 of 8

MODEL	700	ADL Grade	BDL Grade
ACCURACY	Use open sights, fore-end and elbow rest. Use third notch on sight step.		
Test Ammunition:	See Accuracy Index.		
Group Size:	See Accuracy Index.		
Center of Impact:	Not more than 2 inches below, or 4 inches above, or 3 inches either side of point of aim.		
Point of Aim:	6 o'clock on target.		
Range:	100 yds.		
ACTION	Bolt action, center fire, hand operated repeater. Solid frame with take-down stock. Fixed magazine. Bolt cocks as handle lifts. Rifle cocks as bolt handle is lowered to lock action closed. Extracts and ejects as bolt is "opened". Direct action trigger. 2 stop safety. FIRE position - forward. SAFE position - rearward. Rear position of safety locks bolt closed.		
Short Action Calibers	222, 308 243, 6mm 22-250 222, 308 243, 6mm 22-250, 17 Rem. 6.5, 350 Mag.		
Long Action Calibers:	30-06, 25-06 270, 7mm 30-06, 25-06 270, 7mm 264, 300 Mag.		
	Action must feed, fire, extract and eject (include extraction and ejection without firing), satisfactorily with all varieties of ammunition listed as standard for listed calibers in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).		

REVISED 5-9-72

REMINGTON STANDARDS - ARMS

SHEET 2 of 8

MODEL 700		ADL Grade	BDL Grade
ANNOUNCEMENT			
30-06	1962		
270 Win.	1962		
222 Rem.	1962		
7mm Rem. Mag	1962		
264 Win. Mag.	1962		
300 Win. Mag.	1964		
308 Win.	1962		
243 Win.	1962		
25-06 Rem.	1970		
6mm Rem.	1963		
22-250 Rem.	1965		
17 Rem.	1971		
6.5 Rem. Mag.	1969		
350 Rem. Mag.	1969		
BARREL	Round, tapered to breech, crowned, Black color, Medium lustre.		
Material:	Remington specified alloy steel. Stainless steel for 17 Rem. only.		
Bore-Groove:	See Rifling Index.		
Optional Barrel:		w/o Sights	w/o Sights
Markings:	See Marking - Barrel.		
BOLT ASSEMBLY:	3 piece brazed assembly - Bolt body, Bolt head, Bolt handle. Includes Firing Pin Assembly.		
Bolt Plug:	Cover firing pin head. Black color		
Bolt Handle:	Swept back oval shape ball. Checker on upper and lower face of ball. Black color		
Bolt Body:	Bright Steel - damascene finish.		
Bolt Head	Black color.		
Markings:	See Marking - Bolt		
Size:			
Small	222, 17 Rem.		
Short Std.	243, 6mm, 308, 22-250		
Standard	30-06, 270, 25-06		
Short Magnum	6.5, 350, Mag.		
Magnum	7mm, 264, 300 Mag.		

REMINGTON STANDARDS • ARMS

REVISÉ 5.9-72

[illegible]

REMINGTON STANDARDS - ARMS

REVISED 5-9-72

[illegible]

REMINGTON STANDARDS - ARMS

REVISED 5-9-72

MODEL 700		ADL Grade	BDL Grade
MARKINGS - Barrel (Dwg. C-15360)			
Assembly	Left Rear		
Caliber	Left Rear of Remington name.		
Code (Mfg. Date)	Left Rear		
Inspection	Left Rear		
Patent Numbers	Below Remington address.		
Remington Address	Left Side		
Target	Right Rear.		
Test	Right Rear		
Magnaflux	Right Rear		
Other			
MARKINGS - Bolt (Prick-punch mark)			
Bolt Handle Braze	Rear Handle (Center)		
Bolt Head Braze	Left Lug (Center)		
Magnaflux	Right Lug (Center)		
Proof	Bottom Handle (Center)		
Serial Number (1)	Underside (Rear)	Last four (4) numbers only.	
MARKINGS - Receiver (Dwg. C-15360)			
Grade	None		
Model Number	Below Remington Script		
Model Script	None		
Remington Script	Left Side		
Serial Number	Left Side, Front		
Other	Mark "S" and "F" on receiver below and above resp. SAFE and FIRE stop positions of safety.		

SHEET 6 of 8

REMINGTON STANDARDS - ARMS

REVISED 5-9-72

[illegible]

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

BARBER - PRESALE R 0104242

R2505230

REVISED 5-9-72

REMINGTON STANDARDS - ARMS

SHEET 7 of 8

MODEL 700	ADL Grade	BDL Grade
RECOIL PAD		
Calibers:	All Magnum Grades, only. Std. Equipment	
SAFETY		
Location	2 stop position, thumb operated - forward and back. Corrugated, black surface.	
"FIRE" Position	Right rear of Receiver.	
"SAFE" Position	Forward stop position, Marked "F" on receiver.	
	Rearward stop position (block lock position also). Marked "S" on receiver.	
SERIAL NUMBER		
Location	(Start 6,200,000 - Last No. 6,899,999 Ref. See Marking Dwg. C-15360)	
	See MARKINGS - Receiver	
	See BOLT - Markings	
	(Last four (4) numbers only)	
SLING STRAP		
Type - 7/8"	Leather, one piece - purchased, Accessory	Std. Equip.
SLING SWIVEL	See STOCK	
	Accessory	Standard
	(added cost)	Equip.
SIGHTS		
Front	Metal, black color. (Removable).	
Rear	Brass face head (dovetail) with screw (2) fit ramp.	
	Open, U-Notch (with adjustable step).	
STOCK (Assembly)	American walnut, reddish filler, Monte Carlo with cheek piece, Pistol grip with comb cuts and checkered (Custom). See action: Long action, short action caliber use.	
Finish	RK-W	RK-W
Butt Plate	See Butt Plate	
Spacer (white plastic)	No	Yes
Recoil Pad:	(MAGNUM caliber use only)	
Checker (die impressed)	D-14698	D-14697
Dimensions (Nominal - 30-06)	See Below	See ADL Grade
Drop at Heel (from C of barrel)	15/16"	"
Drop at Comb & Monte Carlo (from C of bbl.)	11/16"	"
Length of Pull	13 3/8"	"
Length of Grip	3 3/8"	"
Pitch (from C of barrel)	2 7/8"	"

MODEL 700		ADL Grade		BDL Grade	
STOCK (Continued)					
	Fore-End Cap (black plastic) Spacer (white plastic)		No		Yes Yes
	Grip Cap (black plastic) Spacer (white plastic)		No		Yes Yes
	Swivels (2) 7/8" O.D. (Quick Detachable)		No		Yes
	TRIGGER				
	Pull (Wt.)	Direct action, black metal.	Wide serrated finger piece, full radius.		
	Engagement	3 lbs. Min. - 5 lbs. Max. (with wt. sealed at factory).	Adjustment sealed at factory.		
	TRIGGER GUARD				
	Type	Aluminum alloy, black color	Anodized - High Lustre		Long (with floor plate)
	WEIGHT	(See Gun Length & Weight)			