

DON'T SAY IT—WRITE IT

TO GEORGE MARTINSAFETY MALFUNCTIONS
GALLERYDATE 5-2-75FROM GENE BULLIN

MODEL	MALFUNCTIONS												TOTAL SAFETY MALFUNCTIONS BY MODEL			
	FSR			JO			FD			FOS				SWW		
	705	74	75	705	74	75	705	74	75	705	74	75		705	74	75
40							4									4
1P 100							3									3
540																
541								2	1							3
580													1			1
581							3	2	1							6
582																
100	1						10	74	55							140
700	9						7	19	10	1				1		47
788	4						3	9	3	2	9	4	14	95	53	196
ARLY MALF. TOTALS	14						30	106	70	3	9	4	14	97	53	400

TOTAL SAFETY MAL.

MALFUNCTION MEANINGS

FSR - FIRES WHEN SAFE IS RELEASED - SELF EXPL.

JO - JARS OFF (HAMMER FAILS TO STAY ENGAGED WITH SEAR AND FALLS
DOWN WHEN GUN IS JARRED.)FD - FOLLOWS DOWN (COCKING PIECE FAILS TO PROPERLY ENGAGE WITH SEAR AND FOLLOWS
THE COCKING CAM SURFACE OF THE BOLT TO THE FIRED POSITION).

FOS - FIRES ON SAFE (GUN FIRES WITH SAFE IN "ON" POSITION WHEN TRIGGER IS PULLED).

SWW - SAFETY WON'T WORK - SELF EXPL.

* - 1975 DATA FROM DEC. 26, 1974 TO APRIL 29, 1975 ONLY.