

Orig. 12-7-67

REVISED 9-19-75

REMINGTON STANDARDS - ARMS

SHEET 1 of 3

700 BDL MODEL VARMINT	222 Rem.	223 Rem.	22/250 Rem.	6MM Rem.	243 Win	(2) 25-06 Rem.	308 (3) Win.
Note: All specifications same as M/700 BDL							
EXCEPT AS LISTED HEREIN							
ACCURACY (C to C)							
Max. Group Size (5 Shots) E. S.	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"
All Rifles Must Pass A 5 Shot Specification							
Range	100 yards. Use Accuracy Device.						
Ammunition	(Power-Lock) 50gr. or equiv.	55gr.	55gr.	80gr.	80gr.	87 gr	150 gr.
ACTION	Short	Short	Short	Short	Short	Long	Short
Bolt action, handle operated repeater. Solid frame with long stock. Fixed magazine, latched floorplate for bottom unloading, if desired, 2-stop safety, forward to FIRE position rearward to SAFE position.							
Action must feed, fire, extract, eject (include extraction and ejection without firing), satisfactorily with all varieties of ammunition listed as standard for listed calibers in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).							
ANNOUNCEMENT:							
Varmint Model							
Release to Production:	General Management Approval March 16, 1966. See letter V. G. DeReus to Management dated March 18, 1966.						
(2) Ref: Intro. 1971. See OP	Comm Min No	7-1970 Dated	4-3-70.				
(3) Added Ref. Operations	Committee Development	Schedule	for 1976.				

REVISÉ. 4-6-71

REMINGTON STANDARDS • ARMS

SHEET 2 of 3

MODEL	700 BDL VARMINT	222 Rem.	223 Rem.	22-250 Rem.	6mm Rem.	243 Win.	25-06 Rem.	308 (1) Win.
BARREL (HEAVY):	Round, tapered, colored black. Crowned same as 40X-B. Remington Specification alloy steel.							
Caliber:	See Tabulations.							
Length:	24 inches (All calibers).							
Markings:	Same as M/100							
Sight Holes:	Two (2) one rear taper.							
*Rifling:								
Bore	Min. .219	.219	.219	.219	.237	.237	.250	.300
	Max. .220	.220	.220	.220	.238	.238	.251	.301
Groove	Min. .224	.224	.224	.224	.243	.243	.257	.308
	Max. .2245	.2245	.2245	.2245	.2435	.2435	.2575	.309
Twist	(1 Turn) R. H. 14 inches.	12 inches	12 inches	14 inches	9 1/8 inches	9 1/8 inches	10 inches	12 inches
CAPACITY								
Gun	6	6	5	5	5	5	5	5
Magazine	5	5	4	4	4	4	4	4
RECEIVER:	Short	Short	Short	Short	Short	Short	Long	Short
*See Model Drawings.								
(1) Added Ref. Operations Committee Development Schedule for 1976								

***See Model Drawings.**

(1) Added Ref. Operations Committee Development Schedule for 1976

2-9-71

REVISED

9-19-75

REMINGTON STANDARDS - ARMS

SHEET 3 of 3

MODEL	700 BDL VARMINT	222 Rem.	223 Rem.	22/250 Rem.	6MM Rem.	243 Win.	25-06 Rem.	308 (1) Win.
GUN LENGTH: (Inches)		43 5/8	43 5/8	43 5/8	43 5/8	43 5/8	44 1/2	43 5/8
SCOPE BASES:	Front & Rear	(40X-B type)						
* PACKING: Same as standard Grade except (Shipping)								
Weight - 1 Gun	11 lbs.							
Weight - 2 Gun	20 lbs.							
Weight - 3 Gun	30 lbs.							
Weight - 5 Gun	49 lbs.							
STOCK:	Same as M/700 BDL Except:	modified barrel radius.						
Receiver Cut		Short	Short	Short	Short	Short	Long	Short
WEIGHT:	(with sling)	9 lbs. (dependent upon caliber).						
* Shipping weight revised per	W. W. Fenton (warehouse)							
(1) Added. Reference Operations Committee	Development Schedule for 1976.							