TLW _ 0 4 5 2
Project No. 24/267
S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST
Firecontrol No. A-7 Firecontrol Type: \$7ANDAR 5 Date: 04-10-01  Dry Cycles/Rounds Completed: Stock Type 5. n. n. 1. 2 Engagement at Start .0 / E0  Model No. M/7 Serial No. 7758643 Engagement at End .0 / 28  Trigger Pull at Start of Test (1) 40 (2) 40 (3) 425 (4) 40 (5) 3.75 (6) 40  Average Trigger Pull at Start of Test: 40 Std. Dev. of Trigger Pull at Start of Test:  Trigger Pull at End of Test (1) 45 (2) 4.25 (3) 4.25 (4) 5 (5) 45 (6) 4.5  Average Trigger Pull at End of Test: 4.41 Std. Dev. of Trigger Pull at End of Test:
Additional Notes and Comments  Tester Initials: RVL  Additional Notes and Comments
For additional details on the proper procedures to be used for this Test Procedure refer to:
ANSL/SÄAMI Z299.5-1990
SAAMI Specifications for Standard Jar-Off Test  Jar-Off Test: 12 inch drop onto 1" thick 85 durameter (Shore A) Rubber Matt Firegraficady to fire Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop, fire Primed Case to verify firearm will still function.  12 inch drop (safety in "Fire" position) - one drop per orientation.  Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked  position for all six orientations of the Jar-Off Test
O <u>rientation</u> ISS Unlocked Comments
Barrel Vertical, Muzzle Up:  Barrel Vertical, Muzzle Down:  Pass Fail  Barrel Horizontal, Left side of Stock Up:  Barrel Horizontal, Right side of Stock Up:  Barrel Horizontal, Bottom of Stock Up:  Pass Fail  Barrel Horizontal, Bottom of Stock Up:  Pass Fail  Barrel Horizontal, Bottom of Stock Down:  Barrel Horizontal, Bottom of Stock Down:  Barrel Horizontal, Bottom of Stock Down:
Page 1 of 2 Z101\DROPTEST_REV3.DOC

ET30079

	TLW <u>δ452</u>
	Project No. 24/267
,	S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST
	SAAMI Specifications for Standard Drop Test:
<u>Drop Test</u> :	48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop Fire Primed Case to verify firearm will still function.
48	inch drop (safety in "Safe" position) - one drop per orientation.
Note: for Fi	rearms with the ISS system installed — The Firearms will be set with the
	em in the unlocked position for all six orientations of the Drop Test
Orientation  Barrel Vertical, Muzzle U  Barrel Vertical, Muzzle D	ISS Unlocked Comments  p: Pass Fail 83
Barrel Horizontal, Left sid Barrel Horizontal, Right s Barrel Horizontal, Botton	de of Stock Up: Pass Fail  ide of Stock Up: Pass Fail  of Stock Up: Pass Fail
Barrel Horizontal, Bottom SAAMI Specif	of Stock Down: Past Fall File Control of Stock Down: Past Fall Fall Fall Fall Fall Fall Fall Fal
The contract of the contract o	Drope onto I" thick 85 durameter (Shore A) Rubber Matt Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds.  After each drop Fire Primed Case to verify firearm will still function.  tation Test" (safety in "Safe" position) - one drop per orientation.
<u>. 89</u> 6	Firearms with the ISS system installed - The Firearms will be set with the
<u>ISS syste</u>	m in the unlocked position for both orientations of the Rotation Test.
Oriento	ation ISS Unlocked Comments
Firearm Vertical, Drop so Firearm Vertical, Drop so	o left side of Stock is Up: Pass Fail
Notes: (continue on back of	sheet if necessary)
	Tester's Initials ブレ/ Bレ
	Page 2 of 2 Z101\DROPTEST_REV3.DOO

ET30080