

PROCEDURE

Page _____

GUN DESIGN SPECIFICATIONS SHEETDate Received 11/17/67Model XP-100No. 5DESCRIPTION:Striker Impact TestA7503271Shrouded Bolt Plug

Barrel Length _____
 Caliber _____
 Type of Feed _____
 Other _____

			Design Spec	Tester	Date
I	Headspace as Received		<u>Indent</u>		
II	Proof Test	☒ Yes	<u>Safe</u>	<u>Safe</u>	<u>Off</u>
III	Headspace after Proof		<u>No Fire</u>	<u>No Fire</u>	
IV	Firing Pin Indent (Inches)		<u>No Indent</u>	<u>No Indent</u>	
	1 <u>0.23</u> ⁰¹	6	<u>No Fire</u>	<u>No Fire</u>	<u>End of shroud</u>
	2	7	<u>No Indent</u>	<u>No Indent</u>	<u>became blunt</u>
	3	8	<u>No Fire</u>		<u>and bound</u>
	4	9	<u>No Indent</u>		<u>striker.</u>
	5	10	<u>No Fire</u>		
	Avg. of 10		<u>No Indent</u>		
	Max.		<u>No Fire</u>		
	Min.		<u>No Indent</u>		
	E. V.				
V	Trigger Pull (Lbs)				
	1 <u>2.25</u>	6			
	2	7			
	3	8			
	4	9			
	5	10			
	Avg. of 10				
	Max.				
	Min.				
	E. V.				
VI	Firing Pin Protrusion (in.)				
	(a) Positive				
	(b) Extreme				

Weight of gun - 3.77 lbs81270 Weight of impact device - 3.81 lbs.