

PROCEDURE

Page _____

GUN DESIGN SPECIFICATIONS SHEETDate Received 12-20-78 Model 700DESCRIPTION:# 12669689

Barrel Length _____
 Caliber 243
 Type of Feed _____
 Other _____

Design
Spec

Tester

Date

I	Headspace as Received	<u>SAFE</u>		
II	Proof Test ☒ Yes	<u>ON</u> <u>OFF</u>		
III	Headspace after Proof <u>MIN +.004</u>	<u>6.5 in 6.0 in</u>		
IV	Firing Pin Indent (Inches)	<u>6.0 in 6.0 in</u>		
	1 <u>.0235</u> 6	<u>6.5 in 6.0 in</u>		
	2 <u>.024</u> 7	<u>6.3 in 6.0 in</u>		
	3 <u>.024</u> 8	<u>6.5 in 6.0 in</u>		
	4 _____ 9	<u>BOLT LIFT</u>		
	5 _____ 10	<u>FIRING UNFIRING</u>		
	Avg. of 10 <u>.0238</u>	<u>15.5 in 5.0 in</u>		
	Max. _____	<u>14.5 in 6.0 in</u>		
	Min. _____	<u>17.0 in 7.0 in</u>		
	E. V. _____	<u>15.7 in 6.0 in</u>		
V	Trigger Pull (Lbs)	<u>WEIGHT</u>		
	1 <u>4.50</u> 6	<u>6.6 in 5.0 in</u>		
	2 <u>4.75</u> 7			
	3 <u>4.50</u> 8	<u>LENGTH</u>		
	4 _____ 9	<u>4 1/2 in</u>		
	5 _____ 10			
	Avg. of 10 <u>4.58</u>			
	Max. _____			
	Min. _____			
	E. V. _____			
VI	Firing Pin Protrusion (in.)			
	(a) Positive			
	(b) Extreme			