

PROCEDURE

Page _____

GUN DESIGN SPECIFICATIONS SHEETDate Received 12-20-78 Model 700DESCRIPTION:R 6699871

Barrel Length _____
 Caliber 243
 Type of Feed _____
 Other _____

018-026

		Design Spec	Tester	Date
I	Headspace as Received	SAFE		
II	Proof Test ☐ Yes	ON OFF		
III	Headspace after Proof <u>MIN +.003</u>	5.5" 6.0"		
IV	Firing Pin Indent (Inches)	5.5" 6.0"		
	1 <u>.027</u> 6	5.5" 6.0"		
	2 <u>.0255</u> 7	5.5" 6.0"		
	3 <u>.025</u> 8	5.5" 6.0"		
	4 _____ 9	5.5" 6.0"		
	5 _____ 10	5.5" 6.0"		
	Avg. of 10 <u>.0258</u>	5.5" 6.0"		
	Max. _____	5.5" 6.0"		
	Min. _____	5.5" 6.0"		
	E. V. _____	5.5" 6.0"		
V	Trigger Pull (Lbs)	BOLT LIFT		
	1 <u>4.00</u> 6	FIRE UNFIRE		
	2 <u>4.50</u> 7	10.0" 4.5"		
	3 <u>4.25</u> 8	10.0" 4.5"		
	4 _____ 9	10.0" 4.5"		
	5 _____ 10	10.0" 4.5"		
	Avg. of 10 <u>4.25</u>	10.0" 4.5"		
	Max. _____	10.0" 4.5"		
	Min. _____	10.0" 4.5"		
	E. V. _____	10.0" 4.5"		
VI	Firing Pin Protrusion (in.)	WEIGHT		
(a)	Positive	6 lb. 13 oz		
(b)	Extreme	LENGTH		
		41 3/8 in.		