

MEASURING FIRING PIN INDENT AND TRIGGER PULL

INTRODUCTION

Note: Both measurements are explained together because they ~~are~~ measured simultaneously. *Not Always.*

CHANGE.

right

DEFINITIONS

Firing Pin Indent

Firing Pin Indent The impression made by the firing pin in the primers of shotshells, centerfires, or the rim of rimfire cartridges. *NOT A SENTENCE*
This impression made by the firing pin is measured with the use of copper crushers. The crusher simulates the primers of various ammunition types. *Crusher Hardness?*

Trigger Pull

The amount of force which must be applied to the trigger of a firearm to cause sear or hammer release. It is measured with a pull scale that touches the trigger at the point where the trigger finger would normally rest, with the force applied in an upward angle to the trigger. *glossy of time!*

PURPOSE

Firing Pin Indent

Firing pin indent is measured to insure against misfires chargeable to the firearm. The measurements must fall within the specified limits for the various firearms.

Trigger Pull

Trigger pull is measured to insure that all Remington sporting arms triggers are comfortable in pull for the prospective gun owners.

LAB REQUIREMENTS

- o All firearms brought to the Test & Measurements Lab must have Firing Pin Indent and Trigger Pull measurements taken ~~before~~ testing.
- o A total of five (5) firing pin indents and five (5) trigger pulls must be taken on each firearm.