

GUN# A-3
 SERIAL # 7114 7436
 CAL- 30.06 SPRG.

REMINGTON M/710
 NON-ISS BOLT PLUG
 DAILY TEST DATA SHEET

TRACKING # TLW1349
 PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START.	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.002		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.019, .020, .021		
		TRIGGER/SEAR ENGAGEMENT	Prng .0243, .0261, .0257 Avg. - .0182 / Reset prng. .0202, .0203, .0201 Avg. - .0202		
BL/JS	12-8-03	TRIGGER PULL	4.163 - 4.147 - 4.088 - Avg 4.299 / Std 4.080		
B. Lee	12-8-03	JACK FUNCTION TEST	No Malfunction	40	41
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Torque Scope mount 25 in lb / Scope 40 in lb / Take down screws Top 40 in lb / Lower 25 in lb		
BL/JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Re-measure	engagement - trigger pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar - off		
JS/BL	12-9-03	Re-measure	engagement - trigger pull		
JS/BL	12-10-03	SAAMI DROP W/SCOPE	pass drop w/ scope		
JS/BL	12-10-03	Re-measure	engagement - trigger pull		
JS/BL	12-10-03	RESET TO STD. SPECS.	reset prng. .0223, .0226, .0225 Avg. .0224 Trigger Pull - 4.426 - 4.466 - 4.486 - 4.416 - 4.499 - Avg 4.459		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS