

GUN# A-4
SERIAL # 71147418
CAL- 30.06 SPRG.

REMINGTON M710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.002		
J. Sims	12/5/03	PROOF TEST	O.K	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.018, .021, .020		
BL/JS	12-8-03	TRIGGER/SEAR ENGAGEMENT	Engage .025-.027 Avg - / Sear Lift-.0159 / Reset Eng-.0201, .0204, .0207 / Avg-.0204		
BL/JS	12-8-03	TRIGGER PULL	4.238-4.607-4.382 Avg 4.605 / Sear 4.676		
BL/JS	12-8-03	JACK FUNCTION TEST	NO JACK FUNCTION 25 in lb / scope	40	41
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Torque Scope Mount 25 in lb / scope 40 in lb / Lockdown screws 700 in lb - lower 25 in lb		
BL/JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Re-measure	engagement - trigger Pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar-off		
JS/BL	12-9-03	Re-measure	engagement - trigger Pull		
JS/BL	12-10-03	SAAMI DROP W/SCOPE	pass drop w / scope		
JS/BL	12-10-03	Re measure	engagement - trigger pull		
JS/BL	12-10-03	RESET TO STD. SPECS.	reset eng-.0225, .0219, .0233 Avg-.0225 Trigger Pull- 4.426-4.324-4.469-4.623-4.565 Avg 4.481		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

BARBER - 5.22.06r007324

Confidential - Submitter: 5022-60-0007324 Order Williams v. Remington

ET33812