

GUN# **A-6**
SERIAL # **71147405**
CAL- 30.06 SPRG.

REMINGTON M710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START.	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	002		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	002		
J. Sims	12/5/03	FIRING PIN INDENT	.019, .020, .020		
B. Lee	12-8-03	TRIGGER/SEAR ENGAGEMENT	Engage 0.021, 0.026 / Sear 1.17, .0169 / Reset 0.029, .0201, .0202 Avg. 0.021		
B. Lee	12-8-03	TRIGGER PULL	4.820-5.034-5.218- Avg 5.057 Sear 4.097		
B. Lee	12-8-03	JACK FUNCTION TEST	No Jack Function	40	41
B. Lee	12-8-03	SETUP FOR SAAMI TESTING	Top of Scope Mount 25.0 in lb / Scope 40 in lb / Take down screws 40 in lb - Lower 25 in lb		
B. Lee	12-8-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
B. Lee	12-9-03	Re-Measure	Engage 0.021 - trigger pull		
B. Lee	12-9-03	SAAMI JARR-OFF W/SCOPE	Pass Jar-off		
B. Lee	12-9-03	Re-measure	Engage 0.021 - trigger pull		
B. Lee	12-10-03	SAAMI DROP W/SCOPE	Pass drop w/Scope		
B. Lee	12-10-03	Re-measure	Engage 0.021 - trigger pull		
B. Lee	12-10-03	RESET TO STD. SPECS.	Reset Eng: 0.021, 0.022 Avg. 0.022 Trigger Pull: 4.395-4.472-4.334-4.515-4.437-Avg 4.431		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

BARBER - 5.22.06P007334