GUN# A-1
SERIAL # 71147415
CAL- 30.06 SPRG.

REMINGTON M/710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED	TOTAL RDS. Ø
J. Sims	12/5/03	INITIAL HEADSPACE	.002		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.020, .019, .019		
J. Sims	12-8-03	TRIGGER/SEAR ENGAGEMENT	eng. .0258, .0256, .026 - Avg. .0258; Sear lift .0157 / reset eng. .0204, .0201, .0209 Avg		
BL / JS	12-5-03	TRIGGER PULL	5.198 - 4.993 - 4.886 - Avg 5.019 ~~Reset 4.640 3.998 3.912 Avg 4.183~~ Set 4.114		
B. Lee	12-8-03	JACK FUNCTION TEST	NO MALFUNCTIONS	40	41
JS / BL	12-8-03	SETUP FOR SAAMI TESTING	Torque Scope mount 25 in lb / scope 40 in lb / Take down screws top 40 in lb / Lower 25 in lb.		
BL / JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass rotation		
BL / JS	12-9-03	Re-measure	engagement - Trigger pull		
BL / JS	12-9-03	SAAMI JARR-OFF W/SCOPE	Pass jarr off		
BL / JS	12-9-03	Re-measure	engagement Trigger Pull		
BL / JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/scope		
BL / JS	12-10-03	re measure	engagement / trigger pull		
BL / JS	12-10-03	RESET TO STD. SPECS.	reset eng. .0223 .0229 .0219 Avg. .0224		
			Trigger Pull 4.653 - 4.485 - 4.304 - 4.345 - 4.272 Avg. 4.412		

83

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

ET33852