

Model M-1000 New Design Bolt Lock a Fire Control Evaluation
4-6-91
A. J. Long / J. H. Hanning

CONTROL R6777525

Remington
Standard

Detected R6782713

Detected R6782713

Type of Bolt Lock
Sec. 8.

At	Headspace min.	Firing pin indent	Trigger pull	Bolt Lock Force	At	Headspace min.	Firing pin indent	Trigger pull	Bolt Lock Force	At	Headspace min.	Firing pin indent	Trigger pull	Bolt Lock Force	At	Headspace min.	Firing pin indent	Trigger pull	Bolt Lock Force	At	Headspace min.	Firing pin indent	Trigger pull	Bolt Lock Force
0	0.00	0.00	0.00	0.00	0	0.00	0.00	0.00	0.00	0	0.00	0.00	0.00	0.00	0	0.00	0.00	0.00	0.00	0	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	100	0.00	0.00	0.00	0.00	100	0.00	0.00	0.00	0.00	100	0.00	0.00	0.00	0.00	100	0.00	0.00	0.00	0.00
200	0.00	0.00	0.00	0.00	200	0.00	0.00	0.00	0.00	200	0.00	0.00	0.00	0.00	200	0.00	0.00	0.00	0.00	200	0.00	0.00	0.00	0.00
300	0.00	0.00	0.00	0.00	300	0.00	0.00	0.00	0.00	300	0.00	0.00	0.00	0.00	300	0.00	0.00	0.00	0.00	300	0.00	0.00	0.00	0.00
400	0.00	0.00	0.00	0.00	400	0.00	0.00	0.00	0.00	400	0.00	0.00	0.00	0.00	400	0.00	0.00	0.00	0.00	400	0.00	0.00	0.00	0.00
500	0.00	0.00	0.00	0.00	500	0.00	0.00	0.00	0.00	500	0.00	0.00	0.00	0.00	500	0.00	0.00	0.00	0.00	500	0.00	0.00	0.00	0.00
600	0.00	0.00	0.00	0.00	600	0.00	0.00	0.00	0.00	600	0.00	0.00	0.00	0.00	600	0.00	0.00	0.00	0.00	600	0.00	0.00	0.00	0.00
700	0.00	0.00	0.00	0.00	700	0.00	0.00	0.00	0.00	700	0.00	0.00	0.00	0.00	700	0.00	0.00	0.00	0.00	700	0.00	0.00	0.00	0.00
800	0.00	0.00	0.00	0.00	800	0.00	0.00	0.00	0.00	800	0.00	0.00	0.00	0.00	800	0.00	0.00	0.00	0.00	800	0.00	0.00	0.00	0.00
900	0.00	0.00	0.00	0.00	900	0.00	0.00	0.00	0.00	900	0.00	0.00	0.00	0.00	900	0.00	0.00	0.00	0.00	900	0.00	0.00	0.00	0.00
1000	0.00	0.00	0.00	0.00	1000	0.00	0.00	0.00	0.00	1000	0.00	0.00	0.00	0.00	1000	0.00	0.00	0.00	0.00	1000	0.00	0.00	0.00	0.00