

4-6-81

4-6-81
A. J. Long / J. Hennings

At	Type of Bolt Lock	Sec.	TEST		RIFLES		CONTROL	Remington Standards
			Min. Detent	Detent	Detent	Detent		
0 rounds	Headspace min. +		AL749249	AL744869	AL744915	AL748544	AL747825	
	Firing pin indent		0.02"	0.02"	0.03"	0.01"	0.01"	0.01" - 0.04"
	Trigger pull		4.11 lb	5.00 lb	5.35 lb	5.50 lb	5.10 lb	0.01" - 0.04"
	Bolt Lock Force		3.00 lb	3.00 lb	6.10 lb	6.00 lb	6.00 lb	0.01" - 0.04"
After 100 rounds	Headspace min. +		0.02"	0.02"	0.04"	0.02"	0.02"	0.01" - 0.04"
	Firing pin indent		0.02"	0.02"	0.05"	0.02"	0.02"	0.01" - 0.04"
	Trigger Pull		4.00 lb	4.75 lb	4.88 lb	5.50 lb	5.50 lb	0.01" - 0.04"
	Trigger pull meas. during dry cycle 1							0.01" - 0.04"
	Cycles.							0.01" - 0.04"
	0		5.85 lb	4.50 lb	4.25 lb	4.33 lb	4.25 lb	4.25 lb
	1000		5.50 lb	4.50 lb	4.10 lb	4.17 lb	4.10 lb	4.10 lb
	2000		5.15 lb	4.10 lb	4.10 lb	4.55 lb	4.25 lb	4.25 lb
	3000		5.50 lb	5.00 lb	4.40 lb	4.55 lb	4.25 lb	4.25 lb
	4000		5.15 lb	5.00 lb	4.33 lb	4.10 lb	4.25 lb	4.25 lb
	5000		5.00 lb	4.25 lb	4.38 lb	4.10 lb	4.25 lb	4.25 lb
	6000		5.90 lb	4.50 lb	4.30 lb	4.25 lb	4.25 lb	4.25 lb
	7000		5.50 lb	4.50 lb	4.37 lb	4.10 lb	4.25 lb	4.25 lb
	8000		5.25 lb	4.50 lb	4.10 lb	4.25 lb	4.25 lb	4.25 lb
	9000		5.00 lb	4.15 lb	4.50 lb	4.33 lb	4.25 lb	4.25 lb
	10000		5.50 lb	4.50 lb	4.50 lb	4.10 lb	4.10 lb	4.10 lb