

Product Information

SEYMOUR
OF SYCAMORE INC.
917 CROSBY AVENUE
SYCAMORE, ILLINOIS 60178
PHONE 815/895-9101

Product:

5 Way Corrosion Inhibitor & Lube #16341

General Description & Applications:

A clear lubricant that 1) Displaces moisture, 2) Lubricates 3) Prevents Rust, 4) Cleans and 5) Penetrates. It dispenses as a fine wet spray.

Use it on any metal, indoors or outdoors*, to protect and preserve during manufacturing and storage. Excellent maintenance item for moving parts.

*Outdoor storage would be limited - not long term.

Features:

Benefits:

Lubricates

Reduces friction and stops squeaks.

Penetrates

Frees nuts & bolts, frozen or stuck mechanisms.

Displaces moisture

Dries wet surfaces.

Prevents rust

Preserves metals in use or in storage.

Cleans

Aids in the removal of dirt, oil, grease, rust & scale.

Comes with extension tube

Pin-point application for hard to reach areas.

Film expands & contracts with metal

Protects throughout normal temperature changes

"Creeps"

Migrates to displace moisture and loosen rust and scale.

Technical Info:

5-Way is a stable, oil based, chemically inert compound that is harmless to metals, paints, and most rubber and plastics. It never becomes hard or tacky. It does not contain Silicone.

Additional Info:

This product does not contain an agitator or mixer. Partial removal of 5-Way can be done by wiping, but for complete removal, a solvent must be used. Will do everything WD-40 can do-plus.

MATERIAL SAFETY DATA SHEET

NPCA 1-7

16-341

FOR COATINGS, RESINS AND RELATED MATERIALS

DATE OF PREP. 7-27-77

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-201)

Section I

MANUFACTURER'S NAME Seymour of Sycamore, Inc.

STREET ADDRESS 917 Crosby Avenue

CITY, STATE, AND ZIP CODE Sycamore, Illinois 60178

EMERGENCY TELEPHONE NO. 815-895-9101

PRODUCT CLASS Aerosol

MANUFACTURER'S CODE IDENTIFICATION 16-341

TRADE NAME Seymour 5-Way Corrosion Inhibitor & Lube

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/m ³		
Mineral Spirits	63.7	500	----	0.70	Aerosol
Diethylene Glycol Monobutyl Ether	0.8	---	----	----	Can 40
Propane	11.0	---	----	1.90	P.S.I.
Isobutane	11.0	---	----	2.30	@ 70°F

Section III - PHYSICAL DATA

BOILING RANGE NA VAPOR DENSITY ☒ HEAVIER, ☐ LIGHTER THAN AIR

EVAPORATION RATE ☒ FASTER ☐ SLOWER THAN ETHER PERCENT VOLATILE BY VOLUME 85% WEIGHT PER GALLON NA

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY FLASH POINT Aerosol -100 F. LEL See I

EXTINGUISHING MEDIA Use carbon dioxide dry chemical or foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS Exposure to heat may cause bursting of aerosol can.

SPECIAL FIRE FIGHTING PROCEDURES Water spray may be ineffective. Water may be used to cool containers to prevent bursting. If water is used, fog nozzles are preferable. Wear goggles and self contained breathing apparatus.

SECTION V - HEALTH HAZARD DATA

IMMEDIATE DANGER See II

EFFECTS OF OVEREXPOSURE Inhalation anesthetic Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

Skin or eye contact.

EMERGENCY AND FIRST AID PROCEDURES Fumes - Remove from exposure, restore breathing, keep warm and quiet. Notify physician. Eyes - flush with copious quantities of running water for at least 15 minutes, take to physician for medical treatment. Skin - remove with soap and water, remove contaminated clothing.

Section VI - REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (with water or other) NA

HAZARDOUS DECOMPOSITION PRODUCTS May produce hazardous fumes when heated to decomposition. Fumes may contain carbon monoxide.

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☐ WILL NOT OCCUR

CONDITIONS TO AVOID NA

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN WHEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all source of ignition avoid breathing vapors, ventilate area.

WASTE DISPOSAL METHOD Do not incinerate aerosol, dispose of in accordance with local, state and federal regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

ADDITIONAL PROTECTION AVOID continuous breathing of vapors and spray mist.

VENTILATION Use with adequate ventilation.

PROTECTIVE GLOVES

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT


Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING DO NOT store above 120° F. exposure to heat or prolonged exposure to sun may cause bursting.

OTHER PRECAUTIONS

HEAVY-DUTY INDUSTRIAL PRODUCTS

MAINTENANCE AEROSOLS




5-way corrosion inhibitor & lube

837745-16341

hand cleaner

837745-16342



- CLEANS
- PENETRATES & LUBRICATES
- DISPLACES MOISTURE
- PREVENTS RUST & CORROSION

FEATURES AND BENEFITS:

Safe on all metal • Durable and long-lasting protection - "Creeps" under to displace moisture and loosen rust and scale • Film expands and contracts with metal • Extremely low surface tension • Meets following government specs.: MIL-C-16173D and MIL-C-23411 (Metal corrosion tests), MIS-C-22235A (Stain test).

APPLICATIONS:

Highly effective multi-purpose, rust-preventative penetrant and lubricant for all general and specialized requirements • Tools, working parts and fittings, sports equipment • After machining operations or after alkali cleaning of metal parts • Loosen frozen parts • Indoor and outdoor metal surfaces • Does not contain silicone.

EXTENSION TUBE FURNISHED

1 PINT - NET WEIGHT 11.8 OZ.

DOES NOT contain agitator or mixer.



- QUICKLY REMOVES DIRT, GREASE, PAINT & GRIME
- CONTAINS LANOLIN
- SAFE FOR NORMAL SKIN

FEATURES AND BENEFITS:

A foaming and waterless cream • Quickly dissolves and removes dirt, grease, paint, grime • Prevents chapping and cracking • contains lanolin • Easy removal - dry towel or water rinse if desired • Pleasantly scented • Safe for normal skin.

APPLICATIONS:

Perfect for quick on-the-spot clean ups • Economy size for mechanics work bench or tool box • Practical also for car, garage, boat and shop.

1 PINT - NET WEIGHT 12.5 OZ.

DOES NOT contain agitator or mixer.