

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE



cc: J. G. Williams
J. E. Preiser
P. H. Holmberg
J. P. Linde
G. D. Campbell
J. W. Brooks

Bridgeport, Connecticut
September 4, 1981

TO: C. B. WORKMAN
FROM: W. H. FORSON, JR.
SUBJECT: MODEL REQUIREMENTS - MODEL 700 RESTYLE

To confirm our conversation of this week, model requirements for the revised Model 700 product line are listed below. For planning purposes, the promotional Model 700 is referred to as a Model 700 A. This, of course, is subject to revision.

Model 700-A: (1984 Introduction)

Action

- Model 700 without detachable floor plate.
- No bolt lock; no jewelings on bolt.
- Stamped trigger guard (possibly long as Model 721).
- Model 788 sights.
- Stamped no bind follower.

Stock

- Birch, Classic style.
- No grip cap, fore-end, spacers, sling swivel studs, or checkering.
- Model 788 butt plate.
- Model 788 type wood finish.

C. B. WORKMAN

SEPTEMBER 4, 1981

MODEL REQUIREMENTS
MODEL 700 RESTYLE

Model 700-ADL (1983 Introduction)

In addition to design requirements in our July 14 memo (copy attached) the following additional points were confirmed.

- Improved metal finish.
- Reduced checkering pattern, 18 lines per inch instead of 20.

Model 700 BDL

Action

- Model 700 with steel trigger guard and floor plate.
- No iron sights.
- Redesigned no-bind magazine follower.
- No bolt lock.
- Jeweled bolt.
- Improved metal finish.

Stock

- Walnut with Monte Carlo and cheek piece.
- Wood fore-end tip, rosewood or other contrasting wood.
- No whiteline spacers.
- New laquer finish, medium gloss.
- Full pattern cut checkering, 20 lines per inch.
- Sling swivel studs.
- Model Four type grip cap.
- Present Model 700 BDL butt plate.

Accessories

- Scope mount rings-design to be determined.



WHF:daf