

RIFLE SUMMARY - DIMENSIONS

	<u>Browning</u>	<u>Ruger</u>	<u>S & W</u>	<u>Winchester</u>	<u>Remington</u>
<u>Receiver</u>					
Overall Length (in.)	9.85	9.50	8.40	9.20	8.85
Length Ejection Port (in.)	3.258	3.184	3.335	3.132	3.240
Ring Diameter (in.)	1.375	1.397 X 1.316	1.343	1.333	1.354
Recoil Lug					
Width (in.)	.870	1.040	1.097-1.015	1.165	1.091
Thickness (in.)	.504	.31 - .18 Taper	.57 - .4 Taper	.366	.185
Height (in.)	.425	.252	.354	.420	Varies
Bearing Area (in.) ²	.37	.26	.37	.49	.50
<u>Bolt</u>					
Number Locking Lugs	9	2	2	2	2
Number Gas Vents	1	3	4	2	1
Bolt Face					
Type	All Are Counterbored.				
Depth (in.)	.130	.118	.124	.120	.147
Shroud Condition	Extractor Cut	Extractor Cut	Extractor Cut	Extractor Cut	Solid Ring
Bolt Rotation	60°	90°	90°	90°	90°
Bolt Body Diameter (in.)	.875	.693	.680	.695	.693
Bolt Head Diameter (in.)	.713	.691	.680	.685	.693
Lug Diameter (in.)	.860	.928	.935	.970	.986
Shroud I.D. (in.)	.487	.490	.480	.486	.486
Lug Shear Area (in.) ²	.6	.449	.472	.356	.425
Bolt Travel in Rec. (in.)	4.40	4.54	4.65	4.39	4.84