

MODEL 700 NEW DESIGN SAFETY
NO BOLT LOCK ARM

10-A-21
R.J.L.

				DRY CYCLES												AFTER 500 RDS LIVE FIRE	
				0	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000			
SEAR THREATEN ↓	SEAR FULL ↓	IFT NULL ↓															
1 → .010	.011	.0057	TRIG. PULL SAFE ON OFF	6.1 9.1 9.0	6.3 8.3 8.1	6.3 7.5 8.1	6.3 8.3 8.1	6.1 8.3 8.1	6.4 7.1 5.3	5.9 6.1 5.3	6.4 6.1 4.8	6.2 6.1 4.6	6.2 6.5 5.1	6.2 6.1 4.5	6.0 4.3 3.2		
2 → .010	.0095	.0035	TRIG. PULL SAFE ON OFF	5.7 8.1 7.1	6.0 6.1 8.1	6.2 5.1 8.8	6.2 5.1 8.5	6.1 5.1 5.1	6.1 5.1 6.3	6.1 5.1 4.5	6.1 5.1 5.3	6.1 5.1 5.1	6.1 4.5 4.1	6.1 4.5 4.1	7.5 4.5 3.5		
3 → .010	.011	.006	TRIG. PULL SAFE ON OFF	6.3 7.0 7.5	6.5 7.5 7.5	6.5 7.5 7.5	6.5 7.5 7.5	6.5 7.5 6.6	6.5 5.0 5.3	7.0 5.1 5.8	6.8 5.5 5.5	6.8 5.5 5.5	6.8 5.5 5.5	6.8 5.5 5.5	7.0 4.5 4.0		
4 → .010	.0105	.0045	TRIG. PULL SAFE ON OFF	5.5 8.3 8.8	5.7 8.0 7.6	6.0 8.5 7.7	6.0 8.5 7.7	5.6 8.1 8.5	5.9 8.1 8.8	6.4 8.4 6.5	6.8 8.8 6.8	6.8 8.8 6.8	6.8 8.8 6.8	6.8 8.8 6.8	6.8 8.8 6.8		
5 → .010	.0105	.0045	TRIG. PULL SAFE ON OFF	6.4 8.6 6.8	6.7 8.6 6.5	6.8 8.6 6.6	6.8 8.6 6.6	6.3 7.1 8.1	6.4 8.6 8.8	6.6 8.6 8.6	6.6 8.6 8.6	6.6 8.6 8.6	6.6 8.6 8.6	6.6 8.6 8.6	6.6 8.6 8.6		
AFTER 10,000 CYCLES AND DATA TEST																	
1 → .010	.010	.0065															
2 → .010	.010	.005															
3 → .010	.010	.0065															
4 → .010	.0105	.006															
5 → .010	.010	.0075															