

Start of test

4

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A 6245544Headspace as Received: M 7.002Safe - "ON" - I. 8.50"OFF" - I. 5.50Proof: OK

(93)

2. 8.503. 8.00

(5.4)

2. 5.503. 5.25

Headspace after Proof: _____

Firing Pin Indent(in.)

Sear lift .018
Sear Engagement .0341. .0232. .0223. .023

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

1. 3.752. 4.003. 3.75

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

I-12-82