

NBAR FIRECONTROL DESIGN OBJECTIVES

- USER "FRIENDLY" DESIGN
- IMPROVED TACTILE FEEL OF THE TRIGGER
- IMPROVED TACTILE FEEL OF THE SAFETY
- CUSTOMER ABLE TO OPEN AND CLOSE BOLT WITH SAFETY "ON"
- BOLT LOCKED DOWN IN A "S" CONDITION
- CUSTOMER ADJUSTABLE TRIGGER PULL FORCE ONLY WITHIN
 PRESCRIBED LIMITS
- BOLT STOP RELEASE RELOCATED WITH IMPROVE TACTILE FEEL
- LEFT HANDED VERSION TO BE DESIGNED
- DESIGN FOR MANUFACTURABILITY PRINCIPLES UTILIZED
- DESIGN FOR ASSEMBLY PRINCIPLES UTILIZED
- "SEALED" DESIGN
- RIFLE WILL NOT FIRE IF TRIGGER PULLED AND HELD AS
 SAFETY IS MOVED FROM "S" TO "F"
- ROBUST AGAINST IMPACT
- COMPEL TRIGGER TO SUPPORT POSITION IN MOVING SAFETY
 FROM "F" TO "S"
- "NO LUBRICATION" DESIGN
- ENHANCED CORROSION RESISTANCE

1 of 1
PLAINTIFF'S
EXHIBIT

3121

AL 0023959