

REPORT #820391

REPORT TITLE: M/700 NEW DESIGN TAGGER AND SPRING EVALUATION

4-6-83 PENDULUM DROP TEST RESULTS.
(JO = JAR-OFF)

PAGE #2

R. HOWE

FOOT	GUN SERIAL No.	86341922	86350761	A6338848	A6817650	86341922	REM
DROP	FIRE CONTROL No.	#6	#7	#8	#9	#6 RETEST	4 SPECS
✓	SENSE ENGAGEMENT	.020	.020	.020	.020	.015	.015-.020
1	TRIGGER Pull LBS.						
2	RESULT OF TARGET MEASUREMENTS	4.0	4.0	3.5	4.5	3.0	3.0-5.0
3	SAFE POSITION						
4	S-SAFE F-FIRE	S F	S F	S F	S F	S F	
5	2' MUZZLE FIRST	OK	OK	OK	OK	OK	
6	BUTT "	OK	OK	OK	OK	OK	
7	RIGHT SIDE	OK	OK	OK	OK	OK	
8	LEFT "	OK	OK	OK	OK	OK	
9	TOP "	OK	OK	OK	OK	OK	
10	BOTTOM "	OK	OK	OK	OK	OK	
11	4' MUZZLE FIRST	OK	OK	OK	OK	OK	
12	BUTT "	OK	OK	OK	OK	OK	
13	RIGHT SIDE	OK	OK	OK	OK	OK	
14	LEFT "	OK	OK	OK	OK	OK	
15	TOP "	OK	OK	OK	OK	OK	
16	BOTTOM "	OK	OK	OK	OK	OK	
17	6' MUZZLE FIRST	OK	OK	OK	OK	OK	
18	BUTT "	OK	OK	OK	OK	OK	
19	RIGHT SIDE	OK	OK	OK	OK	OK	
20	LEFT "	OK	OK	OK	OK	OK	
21	TOP "	OK	OK	OK	OK	OK	
22	BOTTOM "	OK	OK	OK	OK	OK	
23	2' MUZZLE FIRST	OK	OK	OK	OK	OK	
24	BUTT "	OK	OK	OK	OK	OK	
25	RIGHT SIDE	OK	OK	OK	OK	OK	
26	LEFT SIDE	OK	OK	OK	OK	OK	
27	TOP "	OK	OK	OK	OK	OK	
28	BOTTOM "	OK	OK	OK	OK	OK	
29	4' MUZZLE FIRST	OK	OK	OK	OK	OK	
30	BUTT "	OK	OK	OK	OK	OK	
31	RIGHT SIDE	OK	OK	OK	OK	OK	
32	LEFT "	OK	OK	OK	OK	OK	
33	TOP "	OK	OK	OK	OK	OK	
34	BOTTOM "	OK	OK	OK	OK	OK	
35	6' MUZZLE FIRST	OK	OK	OK	OK	OK	
36	BUTT "	OK	OK	OK	OK	OK	
37	RIGHT SIDE	OK	OK	OK	OK	OK	
38	LEFT "	OK	OK	OK	OK	OK	
39	TOP "	OK	OK	OK	OK	OK	
40	BOTTOM "	OK	OK	OK	OK	OK	

NEOPRENE STOP

HARD WOOD STOP

REPORT #820391

REPORT TITLE: M/700 NEW DESIGN TRIGGER SCREW AND SPRING EVALUATION
4-6-83 DRY CYCLE RESULTS

PAGE #1

P. Howe

	1	2	3	4	5	6
SERIAL No	B6341922	B635761	A6338848	A6817650		
GUN	#6	#7	#8	#9		
TRIGGER PULL LBS.						
AT 0 CYCLES	5.0	5.4	4.1	4.9		
300 "	4.8	5.5	4.2	5.0		
600 "	4.6	5.5	4.8	4.8		
1000 "	5.0	5.5	4.6	5.0		
2000 "	7.0	7.0	5.5	5.1		
3000 "	7.3	8.0	5.6	4.7		
4000 "	10.0	10.0	7.6	4.9		
5000 "	10.1	10.1	8.0	4.6		
GUN #6 + #7 LUBED W/ TEFLON WET						
5000 AFTER LUBE	5.0	5.0				
6000 CYCLES	4.3	4.5	7.8	4.9		
7000 "	4.0	4.1	8.5	4.5		
8000 "	3.8	4.5	8.7	5.5		
9000 "	3.8	4.4	8.5	5.5		
10,000 "	3.9	4.5	8.3	5.3		
10,000 AFTER LUBE			4.2	4.5		
11,000 CYCLES	4.0	4.3	4.2	4.4		
12,000 "	3.7	4.0	3.5	4.7		
13,000 "	3.8	4.1	3.5	5.0		
14,000 "	3.7	4.0	3.2	4.7		
15,000 "	3.9	4.0	3.5	4.5		
NOTE: ALL TRIGGER PULL LBS. ABOVE ARE A RESULT OF THREE MEASUREMENTS.						
PRESENT REMINGTON SPECS. M/700 TRIGGER PULL - 3.0 TO 5.0 LBS.						
"CONFIDENTIAL by Stipulation and order entered in Isachalis v. Remington Arms, Inc., et al., Supreme Court of the State of New York, County of Westchester, Index No. 9344/95"						