erage tabrace the fridder sesential of no charde

January 27, 1984

Mr. Robert H. Marcouiller, Jr. P.C. Box 56233 Borth Pole, Alaska 99705

Dear Mr. Marcouiller:

Examination has been completed on the Model 700 ADL 270 Win. caliber rifle, serial number B6386381, that you returned to us a short time ago because the rifle fired when you moved the safety from the "safe" to "fire" position.

The returned firearm, which was produced in April of 1982, has been thoroughly examined by our firearms experts who report that it contained our high-pressure proof test, gallery test, and final inspection stampings, indicating that it had successfully passed all our necessary tests prior to shipment. The Control of the Control of the State of the Control of the Cont

The general condition of the gun appeared to be used, and it was noted that a recoil pad, sling swivel stude, and scope mounts had been added after the rifle left our factory. In going over the individual parts, it was noted that the stock contained numerous scratches and mars.

Burner and the sing that it is the single-singlemitial testing of the rifle indicated that if the bolt was closed rapidly, with the safety in the "safe" position, subsequent movement of the safety would cause the firing pin to fall. Further investigation, which included disassembly of the trigger mechanism, disclosed that the trigger connector was broken. Additionally, removel of the firing pin showed burn marks and powder residue on the firing pin tip and shoulder and, brase particles in the bolt threads.

Based upon the powder burns and residue present on the firing pin. the trigger connector breakage resulted from pierced primers. When a primer pierces, an amount of propellant gas blows rearward through The firing pin hole in the bolt, causing the firing pin to be driven reservand. Upon moving rearward, the cocking piece of the firing pin hits the trigger sear-safety cam which in turn strikes the connector 16.

January 27, 1984

This type of problem is generally associated with high-pressure reloads.

Remington Arms Company, Inc. does warranty its products against any defects in materials and workmanship. However, under the circumstances when the damage resulted from a condition beyond our control, we cannot of course, assume any responsibility or liability for the present condition of the rifle, or for your missed trophy. However, we do want to be as helpful as possible to you and, as a gesture of customer good-will, are replacing the trigger assembly in your rifle at no-charge.

Thank you for having afforded us this opportunity to be of service to you, and we trust that our handling meets with your approval.

Sincerely,

J.A. Stekl, Supervisor

- Product Service

JAS:tpp