

5/8/90

After

Trig. Adj.

"JAR OFF TEST"FIREARM # B7532032REPORT #MODEL XP100 R-W.O. #TRIGGER PULL LBS _____ TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

12" DROP
SAFE OFF(V = OK
J.O. = JAR OFF)

BAR. VERT MUZZLE UP

✓

" " " DOWN

✓

BAR HORIZ. BOTTOM UP

JO

" " " DOWN

✓

" " LEFT SIDE UP

✓

" " RIGHT SIDE UP

✓"DROP TEST"

48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP

✓

" " " DOWN

✓

BAR HORIZ. BOTTOM UP

✓

" " " DOWN

✓

" " LEFT SIDE UP

✓

" " RIGHT SIDE UP

✓"ROTATION TEST"

BUT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP . N.A.RIGHT SIDE UP N.A.

XP100R

7th 08 .

2035. +.002 +.003

2032 +.001 +.001

1974 +.003 +.004

223

1730 +.001 +.002

1715 +.001 +.001

#1 B7531730
 #2 B753 1715
 #3 B7531998
 #4 B7532062
 B7532078
 B753 2032
 B753 1974
 B753 2035

[Handwritten squiggle]

[Handwritten squiggle]

[Handwritten squiggle]

SAAMI SPEC.
"JAR OFF TEST"

FIREARM # 87532032

REPORT #

MODEL XPI00R

7n08

W.O. #

TRIGGER Pull LBS 2.9lb TEST TITLE

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A" RUBBER MATT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

BAR. VERT MUZZLE UP

12" DROP
SAFE OFF

J.O.

(V = OK
J.O. = JAR OFF)

" " " DOWN

✓

BAR HORIZ. BOTTOM UP

✓

" " " DOWN

✓

" " LEFT SIDE UP

✓

" " RIGHT SIDE UP

✓

"DROP TEST"
 48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP

✓

" " " DOWN

✓

BAR HORIZ BOTTOM UP

✓

" " " DOWN

✓

" " LEFT SIDE UP

✓

" " RIGHT SIDE UP

✓

"ROTATION TEST"

BUT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP NA

RIGHT SIDE UP NA

SAAMI SPEC.
"JAR OFF TEST"

FIREARM # B7531715

REPORT # _____

MODEL XP100R 223 Rem

W.O. # _____

TRIGGER PULL LBS 3.6 TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A" RUBBER MATT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
BAR. HORIZ. BOTTOM UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
" " LEFT SIDE UP	<u>✓</u>	
" " RIGHT SIDE UP	<u>✓</u>	

"DROP TEST"
 48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	<u>✓</u>
" " " DOWN	<u>✓</u>
BAR. HORIZ. BOTTOM UP	<u>✓</u>
" " " DOWN	<u>✓</u>
" " LEFT SIDE UP	<u>✓</u>
" " RIGHT SIDE UP	<u>✓</u>

"ROTATION TEST"

BUTT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP NA
 RIGHT SIDE UP NA

SAAMI SPEC.
"JAR OFF TEST"

FIREARM # B7532078

REPORT # _____

MODEL XP100R 35REM

W.O. # _____

TRIGGER PULL LBS 3.2 TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A" RUBBER MATT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
BAR HORIZ. BOTTOM UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
" " LEFT SIDE UP	<u>✓</u>	
" " RIGHT SIDE UP	<u>✓</u>	

"DROP TEST"
48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER
OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	<u>✓</u>
" " " DOWN	<u>✓</u>
BAR HORIZ BOTTOM UP	<u>✓</u>
" " " DOWN	<u>✓</u>
" " LEFT SIDE UP	<u>✓</u>
" " RIGHT SIDE UP	<u>✓</u>

"ROTATION TEST"

BUTT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP NA
 RIGHT SIDE UP NA