

## SAAMI DROP TEST

TEST TITLE \_\_\_\_\_

REPORT # \_\_\_\_\_ W.O.# \_\_\_\_\_ DATE 5-30-90MODEL XP100 R SERIAL# B7532032 TRIGGER PULL (LBS.) 4.25COMMENTS CURRENT PROD m/700 FIRE CONTROL

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.  
ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

		1.8"	24"
BARREL VERTICAL, MUZZLE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>

48 INCH DROP (SAFE ON)

NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

BARREL VERTICAL, MUZZLE UP	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	<u>OK</u>

## "ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

LEFT SIDE UP	<u>OK</u>
RIGHT SIDE UP	<u>OK</u>