

SAAMI DROP TEST

TEST TITLE _____

REPORT # _____ W.O.# _____ DATE _____

MODEL 40XBR SERIAL# 054431B TRIGGER PULL (LBS.) 1.5

COMMENTS _____

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.
 ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

* TRIGGER PULL
CHANGED TO 3.5 LBS

BARREL VERTICAL, MUZZLE UP	<u>OK</u>	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>JO</u>	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	<u>OK</u>	<u>OK</u>

48 INCH DROP (SAFE ON)

NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

BARREL VERTICAL, MUZZLE UP	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	

"ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

LEFT SIDE UP	<u>OK</u>
RIGHT SIDE UP	<u>OK</u>